

EXIFutils

Image Metadata Utilities

Command Reference Guide

for
Linux / MacOS X / Solaris

V2.7

Copyright Notice

Copyright © 2000-2006 Hugsan Pty. Ltd. All rights reserved.

Trademark Acknowledgements

All terms or logos used in this manual that are known to be registered trademarks, trademarks, or service marks of entities other than the author are listed below:

Microsoft® Windows 98®, Microsoft® Windows 95®, Microsoft® Windows® 2000, and Microsoft® Windows® XP are trademarks and/or service marks or registered trademarks of Microsoft Corporation or its subsidiaries in the United States and/or in other countries.

Mac OS X is a trademark of Apple Computer, Inc., registered in the U.S. and other countries. The EXIFutils Getting Started Guide is an independent publication and has not been authorized, sponsored, or otherwise approved by Apple Computer, Inc.

Linux is a registered trademark of Linus Torvalds

Red Hat, the Red Hat "Shadow Man" logo, RPM, Maximum RPM, the RPM logo, Linux Library, PowerTools, Linux Undercover, RHmember, RHmember More, Rough Cuts, Rawhide and all Red Hat-based trademarks and logos are trademarks or registered trademarks of Red Hat, Inc. in the United States and other countries.

UNIX is the property of The Open Group.

Sun, Sun Microsystems, the Sun Logo, and Solaris are trademarks or registered trademarks of Sun Microsystems, Inc. in the United States and other countries.

Photoshop is a trademark of Adobe Systems Incorporated.

Flashpix is a trademark of Digital Imaging Group, Inc.

All other trademarks or service marks are the property of their respective owners.

Contents

1	<u>INTRODUCTION</u>	6
1.1	STRUCTURE OF THIS MANUAL	6
1.2	INTENDED AUDIENCE	6
1.3	CONVENTIONS USED IN THIS MANUAL	7
1.4	FEEDBACK	7
1.5	WHAT'S NEW IN V2.7?	8
1.5.1	IMPROVED SUPPORT FOR INTERNATIONAL CHARACTERS SETS	8
1.5.2	READ-ONLY SUPPORT FOR ENCAPSULATED POSTSCRIPT (.EPS) FILES	8
1.5.3	RICOH 'RMETA' CUSTOM FIELDS NOW SUPPORTED.	8
1.5.4	RICOH MAKER NOTES NOW SUPPORTED	8
1.5.5	SUPPORT FOR WINDOWS XP TAG 0x4747	8
1.5.6	MAXIMUM LENGTH OF IP-KEYWORD FIELD INCREASED	8
1.5.7	IMPROVED SUPPORT FOR IPTC CODED CHARACTER SET FIELD (1:90)	8
1.5.8	BUG FIXES	8
2	<u>BASIC COMMAND SYNTAX</u>	10
2.1	TYPES OF COMMAND OPTIONS	10
3	<u>REFERENCING FIELDS USING NICKNAMES</u>	11
3.1	SELECTING MULTIPLE FIELDS	12
4	<u>WORKING WITH DATES AND TIMES</u>	13
4.1	DATES FORMATS	13
4.2	TIME FORMATS	14
4.3	AMBIGUOUS OR INCOMPLETE DATES AND TIMES	14
4.4	CONVERTING BETWEEN EXIF AND IPTC DATE/TIME FORMATS	15
4.4.1	SETTING IPTC DATE AND TIME FIELDS TO THE VALUE OF EXIF DATE/TIME FIELDS	15
4.4.2	SETTING EXIF DATE/TIME FIELDS TO THE VALUE OF IPTC DATE AND TIME FIELDS	15
5	<u>CHARACTER SETS</u>	16
5.1	INTRODUCTION	16
5.2	HOW EXIFUTILS HANDLES CHARACTER SETS	16
5.2.1	USING THE /P OPTION TO SPECIFY CHARACTER SETS	17
5.2.2	USING ENVIRONMENT VARIABLES TO SPECIFY CHARACTER SETS	18
5.2.3	TROUBLESHOOTING CHARACTER SET PROBLEMS	18
5.3	EXIF COMMENT FIELD	19
6	<u>TEMPLATES</u>	20
6.1	SECTIONED TEMPLATES	21

EXIFutils Command Reference

7	COMMAND REFERENCE	24
<hr/>		
7.1	EXIFCOPY	24
7.1.1	DESCRIPTION	24
7.1.2	COMMAND SYNTAX	26
7.1.3	EXAMPLES	27
7.2	EXIFDATE	29
7.2.1	DESCRIPTION	29
7.2.2	COMMAND SYNTAX	30
7.2.3	EXAMPLES	30
7.3	EXIFEDIT	32
7.3.1	DESCRIPTION	32
7.3.2	COMMAND SYNTAX	36
7.3.3	EXAMPLES	38
7.4	EXIFFILE	40
7.4.1	DESCRIPTION	40
7.4.2	COMMAND SYNTAX	41
7.4.3	EXAMPLES	42
7.5	EXIFKEY	44
7.5.1	DESCRIPTION	44
7.5.2	COMMAND SYNTAX	45
7.5.3	EXAMPLES	45
7.6	EXIFLIST	46
7.6.1	DESCRIPTION	46
7.6.2	OUTPUT FORMAT OPTIONS	47
7.6.3	THUMBNAIL IMAGE EXTRACTION	51
7.6.4	META DATA EXTRACTION	51
7.6.5	AUDIO STREAM EXTRACTION	52
7.6.6	FIELD ATTRIBUTE LIST OPTIONS	53
7.6.7	CHARACTER SET LIST OPTIONS	53
7.6.8	COMMAND SYNTAX	54
7.6.9	EXAMPLES	58
8	EXIFUTILS FIELD NICKNAMES	61
<hr/>		
8.1	EXPLANATION OF FIELD LIST FORMAT	61
8.2	FILE ATTRIBUTE FIELDS	62
8.3	EXIF DATE TAKEN COMPONENT FIELDS	62
8.4	STANDARD EXIF FIELDS	62
8.5	TIFF FIELDS	65
8.6	PROPRIETARY MAKE NOTE FIELDS	66
8.7	CANON RAW (.CRW) FIELDS	76
8.8	IPTC FIELDS	78
8.9	RICOH RMETA FIELDS	80
9	SOFTWARE LICENSE AGREEMENT	81
<hr/>		
10	VERSION HISTORY	82
<hr/>		
10.1	VERSION 2.7	82
10.1.1	NEW FEATURES	82
10.1.2	BUG FIXES	82

EXIFutils Command Reference

10.2	VERSION 2.6	82
10.3	VERSION 2.5	83
10.3.1	EXIFEDIT	83
10.3.2	EXIFLIST	83
10.3.3	EXIFCOPY	84
10.3.4	MISCELLANEOUS	84
10.3.5	BUG FIXES	84
10.4	VERSION 2.4	84
10.5	VERSION 2.3	85
10.6	VERSION 2.2	87
10.7	VERSION 2.1	88
10.8	VERSION 2.0	88
10.9	VERSION 1.5	89
10.10	VERSION 1.4	90
10.11	VERSION 1.3	90
10.12	VERSION 1.2	90
10.13	VERSION 1.1.1	91
10.14	VERSION 1.1	91
10.15	VERSION 1.0	91
10.16	VERSION 0.5	91
10.17	VERSION 0.4	92
10.18	VERSION 0.3	92
11	INDEX	93

1 Introduction

1.1 Structure of this manual

The sections in this manual cover the following topics:

Section 1 “Introduction” provides an overview of this manual and the changes that have been made since the previous version of EXIFutils.

Section 2 “Basic Command Syntax” explains the command option formats that are common to all EXIFutils commands.

Section 3 “Referencing Fields Using Nicknames” describes methods used to refer to Meta data (EXIF, IPTC, and RMETA) fields.

Section 4 “Working with Dates and Times” explains the EXIFutils features that assist in manipulating date and time fields.

Section 5 “Character Sets” explains how EXIFutils interprets multinational characters, and how EXIFutils can be configured to interpret and display different character sets.

Section 6 “Templates” explains the use of substitution *templates* in EXIFutils commands.

Section 7 “Command Reference” describes in detail the features and use of each EXIFutils command.

Section 8 “EXIFutils Field Nicknames” provides a reference list of the EXIF fields, IPTC fields, RMETA fields, and file attributes that the EXIFutils can access.

1.2 Intended Audience

This manual is intended for users of the EXIFutils who understand the basic concepts of the EXIFutils and want detailed information on the use of each command. It assumes that the reader has a working knowledge of the use of Linux/UNIX systems. In particular it is assumed that the reader understands:

- The use of at least one UNIX command shell,
- How to redirect the output of a command into a file,
- How to pipe the output of one command into another command,
- The use of quotes and wildcards on the command line.

EXIFutils Command Reference

1.3 Conventions Used in this Manual

The following conventions are used in this manual.

`myphoto.jpg` Text in the *Courier New* font represents examples that must be typed exactly as shown.

`field-list.txt` Text in *Italicized Courier New* font represents text for which you must substitute an appropriate value, for example in the following code fragment:

```
-u "your name"
```

you should replace *"your name"* with your own name.

[] Square brackets surrounding text in a command description indicate that the text is optional. For example, if a command is shown as having the following option:

```
[-t]
```

then the `-t` option is optional and need not be entered.

[a|b] Indicates that you must enter either `a` or `b`. For example, if a command is shown as having the option:

```
-t [a|r]
```

then you must enter either

```
-t a
```

or

```
-t r
```

... The ellipse symbol *"..."* indicates that the item preceding it can be repeated multiple of times. The example below indicates that multiple file names can be entered separated by commas:

```
filename,...
```

\ A backslash character at the end of a line indicates that whatever follows on the next line is a continuation of the same command. Example:

```
exiflist -o l -f make,model \  
my-file.jpg
```

is the same as entering:

```
exiflist -o l -f make,model my-file.jpg
```

1.4 Feedback

If you have any feedback on the content or structure of this manual, or if you have any suggestions on how the EXIFutils can be improved, please send email to: support@hugsan.com.

1.5 What's New in V2.7?

This section describes the new features introduced in V2.7, and changes to existing features.

1.5.1 Improved Support for International Characters Sets

- Added support for viewing and editing Windows XP UNICODE fields. The Windows XP fields are:
 - `xp-title-text`
 - `xp-title`
 - `xp-comment`
 - `xp-author`
 - `xp-keyword`
 - `xp-subject`
- Added `-u` option to `exifedit` to specify that EXIF Comment fields are to be stored in UNICODE (previous only ASCII comments were supported). See Section 5.3 “EXIF Comment Field” for more information.
- Improved support for international characters in EXIF and IPTC text fields. The `-p` option has been added to `exifcopy`, `exifile`, `exifedit`, and `exiflist` to specify the character sets to be used to interpret EXIF and IPTC text fields. Environment variables can also be used to specify characters sets. Added `-i` option to `exiflist`, to display the character sets being used. See Section 5 “Character Sets” for more information.

1.5.2 Read-only Support for Encapsulated Postscript (.eps) Files

Read-only access to Meta data in Encapsulated Postscript (`.eps`) files is now supported by `exiffile`, `exiflist` and `exifcopy`. Editing of `.eps` files with `exifedit` and `exifdate` is not supported.

1.5.3 Ricoh 'RMETA' Custom Fields now supported.

Ricoh Pro G3 GPS-capable camera allow the use to define the names and values of up to five custom fields. EXIFutils now supports reading of these fields (see Section 8.9 for a list of RMETA fields).

1.5.4 Ricoh Maker Notes now supported

Ricoh Specific Maker Note fields are now readable and editable.

1.5.5 Support for Windows XP Tag 0x4747

The Windows XP Digital Image Pro Tags field (tag 0x4747) is now supported.

1.5.6 Maximum Length of ip-keyword field increased

The maximum length that of text strings that can be entered in the `ip-keyword` field has been increased fom 32 to 1999 characters.

1.5.7 Improved support for IPTC Coded Character Set field (1:90)

A list of defined values had been added for the IPTC Coded Character Set field (1:90), nickname `ip1-char-set`.

1.5.8 Bug Fixes

- Fix bug where two fields had the same nickname (`n3-color-mode`). Second occurrence of the field was renamed to `n3-color-mode2`.
- Make handling of invalid 'next IFD' offset pointers more robust. In previous versions invalid offset pointers cause a "too many format errors" message and resulted in incomplete EXIF data.
- Fix bug in handling of TIFF strip offsets and lengths with datatype SHORT.

EXIFutils Command Reference

- Fix bug in `exiflist -t` option that caused extracted thumbnail to be incorrect for some Nikon images. The problem occurred when there were two thumbnails in the image, one of which was in the Nikon Maker note.
- Rename "Nikon NEF Thumbnail" IFD to "Nikon Thumbnail" as this IFD can also appear in JPEG files.
- Fix bug in editing files containing Thumbnails embedded in Nikon Maker Notes
- Fix bug that caused incorrect values to be set when IPTC values were being both set and used as template values in the same `exifedit` command.
- Improve validation of command arguments containing `@` file input as invalid values could cause the program to crash.
- `exifedit` would not accept `exif-ver` field values higher than version "220". It will now accept any minor version of V2.2, i.e. "220", "221,... "229".

2 Basic Command Syntax

This section provides a brief overview of the command formats common to all EXIFutils commands. These guidelines are correct when using the Windows Command prompt, and when using UNIX command shells based on the Bourne shell. With other command shells and scripting languages the format of the commands may vary. Refer to the documentation provided with your command shell for more information.

The basic format of all commands is:

```
commandname option option option filename filename
```

commandname is the name of the EXIFutils command being executed, eg: `exiflist`.

option is an option that changes the behaviour of the command. There may be no options, one option, or multiple options. All options start with a '-' character.

filename is the name of a file on which the command will operate. Depending on the command there may no *filenames*, one *filename*, or multiple *filenames*. For some EXIFutils commands/options the *filename* can also be the name of a directory, in which case all files in that directory will be processed.

2.1 Types of Command Options

Command *options* can take one of two different formats:

- **Simple options:** consist of a '-' followed by a single character that identifies the option being used. The presence of the option affects the behaviour of the command. For example, the '-q' option on `exiflist` sets 'quiet mode' to suppress warning messages.
- **Complex options:** Like simple options, complex option start with a '-' followed by a single character that identifies the option. However complex options are followed by an *option string* that further controls the action of the option. For example, the '-f' options on `exiflist` specifies a list of fields to be displayed. The '-f' is therefore followed by a string containing the field list, eg:

```
exiflist -f description,make,model myfile.jpg
```

If the option string contains any of the following characters – " , ; [] " – then the whole option string must be surrounded by quotes:

```
exiflist -f "description, make, model" myfile.jpg
```

```
exifedit -a "comment=I took this photo" myfile.jpg
```

If the option string contains quote characters, then each quote must be preceded by the escape character "\" so that the command does not confuse this quote as marking the end of the option string:

```
exifedit -a "comment=\"I took this photo, too\", shutter=2" myfile.jpg
```

3 Referencing Fields Using Nicknames

Several of the EXIFutils commands allow you to specify a list of fields to display, edit, copy, or delete. To provide an easy way of referring to EXIF fields, the EXIFutils assign a *nickname* to each EXIF, IPTC, and RMETA field. A complete list of field nicknames is provided in Section 8.

In addition to the fields defined by the EXIF and IPTC Specifications, EXIFutils provides additional nicknames that represent other information. There include:

- File attribute information (see Table 1 File Attribute Nicknames)
- Individual parts of the EXIF Date Taken field (see Table 2 EXIF Date Taken Subfield Nicknames)
- The names of files created by the EXIFutils (see Table 3 Created File Nicknames)

Table 1 File Attribute Nicknames

Nickname	Description
file-name	The name of the image file <i>excluding</i> the directory path, eg <code>myphoto.jpg</code>
file-name-full	The name of the image file <i>including</i> the directory path, eg <code>/HolidayPhotos/myphoto.jpg</code>
file-base	The part of the image file name that precedes the last dot '.'. For example, if the file-name is 'myphoto.jpg', then file-base will contain 'myphoto'.
file-ext	The file name extension, i.e. the part of the file name that follows the last dot '.'. For example, if the file-name is 'myphoto.jpg', then file-ext will contain 'jpg'.
file-dir	The directory in which the image file is located, eg <code>/HolidayPhotos</code>
file-size	The size of the file in bytes
file-date-mod	The date/time that the file was last modified. The date is in EXIF standard format, i.e. "YYYY:MM:DD HH:MM:SS"
file-date-created ¹	The date the file was created. The date is in EXIF standard format, i.e. "YYYY:MM:DD HH:MM:SS"

Table 2 EXIF Date Taken Subfield Nicknames

Nickname	Description
yyyy	Year part of <code>date-taken</code> field. Four digits. eg: "2005"
yy	Year part of <code>date-taken</code> field. Two digits. eg: "05"
mm	Month part of <code>date-taken</code> field. Two digits. eg: "12"
mmm	Month part of <code>date-taken</code> field. Three letters. eg: "dec"
dd	Day part of <code>date-taken</code> field. Two digits. eg: "31"
hr	Hour part of <code>date-taken</code> field. Two digits, using 24 hour clock. eg: "23"
min	Minute part of <code>date-taken</code> field. Two digits. eg: "59"
sec	Seconds part of <code>date-taken</code> field. Two digits. eg: "45"

NOTE: If the `date-taken` field is not present in a file, then the above nicknames will return no value.

¹ `file-date-created` is only available on Windows systems. On MacOS X, Linux, and Solaris systems this field will contain the date of last state change of the file.

EXIFutils Command Reference

Table 3 Created File Nicknames

Nickname	Description
file-name-audio	The default name of the audio file that will be created by the <code>exiflist -w</code> command
file-name-backup	The name of the backup file that will be created by the <code>exifcopy</code> and <code>exifedit</code> commands.
file-name-exi	The default name of the EXIF Save file that will be created by the <code>exiflist -e</code> command
file-name-thumb	The default name of the thumbnail file that will be created by the <code>exiflist -t</code> command

3.1 Selecting Multiple Fields

In addition to specifying individual field names, the `exiflist` command provides two quick ways to select multiple EXIF and IPTC fields:

- **Wildcards:** a wildcard character can be used to select all fields whose nickname start with a certain string. For example `'gps-*` will select all GPS related fields because the nicknames of all GPS related fields start with `'gps-`. The wildcard character `'*` can only appear at the end of the string.
- **Special Nicknames:** There are two special nicknames that can be used to select commonly used groups of fields:
 - `exif-common:` `'exif-common'` is predefined to select the most commonly used EXIF fields. Refer to Section 8 for a list of fields that are included by `exif-common`.
 - `iptc:` `'iptc'` is predefined to select all IPTC (Dataset 2) Editorial fields. Refer to Section 8.7 for a complete list of IPTC fields.

4 Working with Dates and Times

EXIF date/time fields are stored in a different format to IPTC date and time fields. All EXIF date/time fields include both the date and the time, in the following format:

“YYYY:MM:DD HH:MM:SS”, eg: “2004:01:27 21:53:00”

All EXIF date/time fields contain both the date and the time. You cannot omit the time.

IPTC dates and times are stored in separate fields, eg the `ip-date` and `ip-time` fields.

IPTC date fields are stored in the following format: “YYYYMMDD”, eg: “20040127”

IPTC time fields are stored in the following format: “HHMMSS+/-ZZZZ”, eg: “212300+10000”

where `HHMMSS` is the time in the local timezone, and `+/- ZZZZ` indicates the timezone. For example, “090000-0500” represents 9:00am in New York (5 hours ahead of GMT/UTC).

You can use the `exifedit` command to set the value of date, time, and date/time fields. When you are setting the value of a date, time, or date/time field, `exifedit` does not require that the date and/or time be entered in the format in which it will be stored. `exifedit` accepts a number of date/time formats and converts them to the format required by the field you are setting.

The sections that follow describe the date/time formats that are accepted by `exifedit`.

4.1 Dates Formats

Table 4 shows the date formats that are accepted by `exifedit`.

Table 4 Accepted Date Formats

YYYY- <i>MMM</i> -DD
DD- <i>MMM</i> -YYYY
DD- <i>MM</i> -YYYY
YYYY- <i>MM</i> -DD
DDMMYYYY
YYYYMMDD
YY- <i>MM</i> -DD
DD- <i>MM</i> -YY
YYMMDD
DDMMYY

where:

- `YYYY` is the year, eg: 2004
- `YY` is the year within the century, eg: “04”
- `MM` is the month number, eg: 05 for May
- `MMM` is the three-character month abbreviation. Valid values are “Jan”, “Feb”, “Mar”, “Apr”, “May”, “Jun”, “Jul”, “Aug”, “Sep”, “Oct”, “Nov”, and “Dec”. Values are not case sensitive; for example “FEB” and “feb” are valid months.
- `DD` is the day of the month, eg: 01

Where a dash separator is shown in Table 4, any of the following separators will be accepted: “:”, “.”, or “/”. For example “01:04:2004” and “01/04/2004” are valid dates.

EXIFutils Command Reference

4.2 Time Formats

Table 5 shows the time formats that are accepted by `exifedit`.

Table 5 Accepted Time Formats

HH-MM-SS
HHMMSS
HH-MM
HHMM
HH-MM-SS±ZZZZ
HHMMSS±ZZZZ
HH-MM±ZZZZ
HHMM±ZZZZ
HH-MM-SS ±ZZZZ
HHMMSS ±ZZZZ
HH-MM ±ZZZZ
HHMM ±ZZZZ

where:

- HH is the hour in 24 hour notation, eg: “13” means 1pm
- MM is the minutes within the hour, eg: “56”
- SS is the seconds within the minute, eg: “12”
- ±ZZZZ is the timezone, eg: “+0500”, “-1000”.

Where a dash separator is shown in Table 5, the following separators will be accepted: “:”, “.”, or “/”. For example “12:04:00”, “12.04.00” and “12/04/00” are valid times.

When no SS (seconds) value is specified, an SS value of “00” will be assumed. Where no timezone is specified a time value of “+0000” will be assumed.

4.3 Ambiguous or Incomplete Dates and Times

If an incomplete or ambiguous date or time value is specified, the following rules will be used to interpret the value:

- If a date/time field is being set and only a date value has been supplied, the time part of the field will be set to midnight (00:00:00). If you only supply a time for a date/time field, an error will be reported and the field not set.
- If no timezone is specified for a field that requires a timezone, then GMT is assumed (i.e. +0000)
- If the ‘seconds’ part of a time value is omitted then a ‘seconds’ value of ‘00’ is assumed.
- If a two-digit year is specified (eg: “04”, “99”) `exifedit` will attempt to select the correct century. If the two-digit year is less than “20” the date is assumed to be in the 21st century, eg. “04” is assumed to mean “2004”. If the two-digit year is “20” or greater it is assumed to be in the 20th century, eg: “99” is assumed to be “1999”.

Note that in some cases it will not be possible for EXIFutils to unambiguously determine your intended value. For example, the value “23:59:59” is unambiguously a time value, but “04:10:01” can either be October 1st 2004, or a time in the early morning (04:10:01AM). In cases where the specified value is both a valid date and a valid time, EXIFutils will look at the type of field being set to determine what was intended. If the field being set is a date field or a date/time field, the value will be interpreted as a date. If the field being set is a time then the value will be interpreted as a time.

EXIFutils will also attempt to interpret dates in both the American ‘month first’ format (eg MM:DD:YY) and the international format (DD:MM:YY), however it is not always possible to determine which is intended. For example, 03:01:04 could mean either March 1st 2004 or January 3rd 2004. In these cases EXIFutils assumes the international format as it most closely matches the date formats used by EXIF and IPTC fields.

4.4 Converting Between EXIF and IPTC Date/Time Formats

It is sometimes necessary to copy EXIF date/time field values into IPTC date and time fields, and vice versa. EXIF date fields contain both the date and time, whereas IPTC fields have separate fields for dates and times. To simplify this task, EXIFutils has been designed to automatically convert between EXIF and IPTC date time formats.

4.4.1 Setting IPTC Date and Time fields to the value of EXIF date/time fields

An IPTC date field (eg: the `ip-date` field) can be set to the date part of the EXIF `date-taken` field by simply assigning the EXIF field value to the IPTC field, for example:

```
exifedit -a "ip-date=[date-taken]" myfile.jpg
```

`exifedit` will automatically extract the date part of the `date-taken` field and convert it to the correct format for the `ip-date` field.

Similarly, an IPTC time field (eg `ip-time`) can be set to the time part of the EXIF `date-taken` field, for example:

```
exifedit -a "ip-time=[date-taken]" myfile.jpg
```

`exifedit` will extract the time part of the `date-taken` field and convert it to the IPTC time format. Note that EXIF date/time fields do not contain any time zone information, unlike IPTC time fields. `exifedit` allows you to add time zone information when setting an IPTC time field, for example:

```
exifedit -a "ip-time=[date-taken] +1000" myfile.jpg
```

4.4.2 Setting EXIF date/time fields to the value of IPTC date and time fields

EXIF date fields (eg `date-taken`, `date-modified`) contain both a date and a time portion. IPTC Meta data contains dates and times in separate fields (eg: `ip-date`, `ip-time`). `exifedit` allows you assign EXIF date fields to the combined value of IPTC date and time fields. For example, to set the EXIF `date-taken` field to the date and time specified in the `ip-date` and `ip-time` fields, use the following command:

```
exifedit -a "date-taken=[ip-date] [ip-time]" myfile.jpg
```

`exifedit` automatically converts the IPTC date and time fields into the format required by the EXIF `date-taken` field.

5 Character Sets

5.1 Introduction

A “character set” is an encoding scheme that defines how text characters are stored as binary values. There are many different “standard” character sets that can be used to store text data in files.

The EXIF Specification states that EXIF text fields are to be stored using the “7 bit ASCII” character set, which means that only unaccented English characters and punctuation marks can be used². The IPTC Standard supports a wide variety of character sets, but the mechanism is limited.

As a result many image editing applications ignore the character sets required by the EXIF and IPTC Standards. Instead they store text data using extended character sets that allow the use of a wide range of non-English characters. It is not always possible to determine which character set was used to store the EXIF and IPTC data in an image file.

The character set most widely used for EXIF and IPTC fields is the Latin1 character set (ISO8859-1) which allows the representation of more than 40 Western European languages. EXIFutils therefore by default assumes that EXIF and IPTC fields are stored using Latin1, but provides the option to use different character sets if required.

The sections that follow describe how EXIFutils handles characters sets, and how the user can specify the character set to be used.

5.2 How EXIFutils Handles Character Sets

EXIFutils commands convert all character strings extracted from both EXIF and IPTC fields into a common character set for internal processing and for display. In EXIFutils terminology, this is called the **Command** character set. This is the character set that will be used when outputting text to the command terminal window or a file. It is also the character set that is used to interpret text files that are read by EXIFutils (eg when a template file is passed as a parameter to `exiflist`). The command character set must therefore match the character set that that the underlying operating system expects.

To correctly read, set, and display text strings, EXIFutils needs to know the character set to use for EXIF fields, IPTC fields, and the Command Character set. The default character sets used by EXIFutils are shown in Table 6. These defaults can be overridden using in the following ways:

- using the `-p` option on the command line
- setting EXIFutils environment variables

Table 6 Default Character Sets

Platform	EXIF Character Set	IPTC Character Set	Command Character Set
Microsoft Windows	LATIN1	LATIN1	ANSI Code Page ³ (except when <code>exiflist</code> is writing directly to the Command Prompt window, in which case the OEM Code Page is used).
Mac OSX			LATIN1 (ISO8859-1)
Linux			
Solaris			

² The EXIF comment field is an exception to this rule. It can be stored in either ASCII or UNICODE. Refer to Section 5.3 “EXIF Comment Field” for more information.

³ On Windows, character sets are translated by Code Pages. There are two special code pages defined in the system; the default ANSI Code Page, and the OEM Code Page.

EXIFutils Command Reference

5.2.1 Using the `-p` Option to Specify Character Sets

The `exifcopy`, `exifedit`, `exiffile`, and `exiflist` commands all accept the `-p` option to specify the character sets to be used. The `-p` has the following form:

```
-p cmd=charset,exif=charset,iptc=charset
```

where *charset* is the name of a valid character set. Any of the three character set types (`cmd`, `exif`, or `iptc`) may be omitted, in which case they will take the default value, or the values specified via environment variables (see 5.2.2 “Using Environment Variables to Specify Character Sets”). Note that on the `exifedit` command, the `-p` options must be before the `-a` (add fields) option.

Table 7 shows commonly used character set names, including special values defined by EXIFutils. EXIFutils will accept any character set name listed by the standard `iconv -l` command, although not all character sets will produce meaningful results. The Command (`cmd=`) character set cannot be set to UNKNOWN.

Table 7 Valid Character Set Names

Character Set Name	Comments
LATIN-1 or LATIN1	Code Page 28591 on Windows
UTF-7 or UTF7	
UTF-8 or UTF8	
MAC	Mac Roman character set. Commonly used on Mac OSX systems.
OEM	Default OEM Code Page (Windows only)
ACP	Default ANSI Code Page (Windows only)
<i>number</i>	The number of any Code Page that is present on the system (Windows only)
Special Values Defined by EXIFutils	
UNKNOWN	Character set is not known. EXIFutils will not perform any translation. Not valid as a Command Character set (i.e. <code>cmd=unknown</code> is not valid).
LOCALE	The default character set for the current locale (OSX, Linux, Solaris only)

The following are examples of valid `-p` option settings:

```
-p exif=utf8,iptc=mac
-p
cmd=locale,exif=utf7,iptc=unknown
-p exif=latin1
-p iptc=unknown
```

While EXIFutils will accept any valid character set name only characters sets which meet the following criteria will function correctly:

- the lower order characters (0x00 to 0x7f) are the standard ANSI characters,
- there are no embedded null bytes (i.e. null can be used to represent the end of the string).

EXIFutils Command Reference

5.2.2 Using Environment Variables to Specify Character Sets

If the same character sets are to be used repeatedly, environment variables can be used to permanently set the character set so that the `-p` option does not need to be included on every command.

Table 8 shows the environment variables used to set EXIFutils character sets. If an environment variable and the `-p` option are used, then the `-p` option overrides the environment variable.

Table 8 Character Set Environment Variables

Environment Variable	Meaning
<code>EXIFUTILS_CS_CMD=charset</code>	Equivalent to <code>-p cmd=charset</code>
<code>EXIFUTILS_CS_EXIF=charset</code>	Equivalent to <code>-p exif=charset</code>
<code>EXIFUTILS_CS_IPTC=charset</code>	Equivalent to <code>-p iptc=charset</code>

If both the `-p` option and the equivalent environment variable are specified, then the `-p` option setting is used.

5.2.3 Troubleshooting Character Set Problems

If EXIF or IPTC text values are not being displayed correctly, then it is likely that one or more character sets have not been set correctly. The most likely problem is that the character set used to store the EXIF or IPTC value is different to the EXIFutils default character set (LATIN1). The most common character sets other than LATIN1 used in storing text values are UTF8 and MAC, the later being most likely if the file was created on a MacOS X System.

To determine if this is the case, try changing the character set to one of these other values. For example, if IPTC text fields are not display correctly, try one of the following:

```
exiflist -p iptc=mac myfile.jpg
exiflist -p iptc=utf8 myfile.jpg
```

If neither of these work, contact EXIFutils support for assistance (support@hugsan.com), sending a sample of the image file.

EXIFutils Command Reference

5.3 EXIF Comment Field

The EXIF comment field (nickname `comment`) can be stored using either plain ASCII text (which only allows Western European characters), or UNICODE (which supports a wide range of international characters)⁴. By default the comment field will be stored using ASCII.

To store the `comment` field using UNICODE, use the `-u` option on the `exifedit` command. For example:

```
exifedit -u -a comment=hello myfile.jpg
```

Alternatively, if you want `exifedit` to always use UNICODE for the comment field, set the `EXIFUTILS_UNICODE_COMMENT` environment variable to 'Y'. Refer to the documentation for your operating system for details of how to set environment variables.

Note that the character set used to store the EXIF comment field is not affected by the `-p exif=charset`, it is only affected by the `-u` option and the `EXIFUTILS_UNICODE_COMMENT` environment variable.

⁴ The EXIF Specification also allows use of the JIS Japanese character set, but this is not supported by EXIFutils.

6 Templates

Templates are a powerfully feature that allows you to substitute field values (EXIF, IPTC, RMETA), and file attribute values into a character string. Three EXIFutils commands allow you to specify a template in place of a fixed character string (Table 9).

Table 9 Command Options That Accept Templates

Command	Option	Option Description	Use of Template
exifedit	-a	Add EXIF field to image	The value to which a field is set can be specified as a template.
exiffile	-n	Rename file	The name to which an image file is renamed can be specified as a template.
exiflist	-s	Set output template	The template defines the output format used to display fields.
	-t	Extract thumbnail	The template specifies the name of the file into which the thumbnail is extracted.
	-w	Extract audio stream	The template specifies the name of the file into which the audio stream is extracted.
	-e	Extract Meta data	The template specifies the name of the file into which the Meta data is extracted.

In its simplest form a *template* is a character string into which values are substituted. A template character string can contain:

1. markers that indicate where field values are to be inserted
2. formatting characters
3. other text

A *marker* is any valid EXIFutils field nickname surrounded by square brackets, eg “[f-number]”. See Section 8 for a complete list of nicknames.

Formatting characters are special characters preceded by a back-slash character “\”. Valid formatting characters are shown in Table 10.

Table 10 Template Formatting Characters

Character	Meaning
\n	New line character
\r	Carriage Return ⁵
\t	Tab character
\\	Backslash character

The EXIFutils commands evaluate a template by scanning for markers and replacing them with the values of the corresponding fields. Any quote characters within a substituted field value will be preceded by a backslash escape character “\”. If the field name specified in the marker is a valid field name, but that field is not present in the image file, then a empty string is substituted. Formatting characters are replaced with the corresponding format character. Any sequence of characters surrounded by square brackets that is not a recognized nickname will be left unchanged.

⁵ Carriage return characters are used to indicate a new line on MacOS X systems.

EXIFutils Command Reference

Example 1

The `exifedit` command below sets the value of the `comment` field based on the value of the `shutter speed` and `f-number` fields:

```
exifedit -a "comment=Shutter: [shutter]\tF-stop: [f-number]\n" photo.jpg
```

If the value of the `shutter` field is "1/125", and the value of the `f-number` field is "5.6", then when the above template is evaluated, the `comment` field will be set to the following string:

```
Shutter: 1/125,    F-stop: 5.6
```

Example 2

The `exiffile` command below renames an image file so that the new file name contains the camera model followed by the original file name:

```
exiffile -n [model]-[file-name] photo.jpg
```

If the value of the `model` field is "NIKON D1X", then the resulting file name will be:

```
NIKON D1X-photo.jpg
```

6.1 Sectioned Templates

To provide greater control over the output format when displaying fields from multiple files, the `exiflist -s` option accepts a more advanced form of template, called a *sectioned template*. A sectioned template has all the features of a basic template but in addition can be divided into three sections:

- The *head* section, which contains text that is to be displayed once, before fields from any file are displayed
- The *file* section, which contains text that is to be displayed once for each file
- The *tail* section, which contains text that is to be displayed once, after all files have been displayed

These sections allow header and trailer information to be displayed before and after the details of the files being displayed.

Section markers in the template indicate the beginning of each section:

```
[EXIF-HEAD] ←
lines to be display once, before the first image file is displayed
[EXIF-FILE] ←
lines to be displayed once for each image file that is displayed
[EXIF-TAIL] ←
lines to be display once, after the last image file has been displayed
```

Section markers

Any section can be omitted if not required. If no section markers are included, then all lines in the template are considered to be in the *file* section. The section markers are not shown in the resulting output.

EXIFutils Command Reference

Example 3

The commands and templates below produce an HTML page that contains a table with headings on each column, and one row for each image file in a directory. Each row will contain the image file name as a web link, the time the image was taken, its file size, and image resolution. The following `exifedit` command and template will achieve this:

```
exifedit -o t -s @template.txt mydir > photolist.html
```

template.txt contains:

```
[EXIF-HEAD]
<HTML>
<HEAD>My Photographs</HEAD>
<TABLE ID="Table1" BORDER=1 CELLSPACING=3 CELLPADDING=1 WIDTH=725>
<TR>
  <TD>File Name</TD>
  <TD>Date/Time</TD>
  <TD>File Size</TD>
  <TD>Dimensions</TD>
</TR>
[EXIF-FILE]
<TR>
  <TD><a href="[file-name-full]">[file-name]</a></TD>
  <TD>[date-taken]</TD>
  <TD>[file-size]</TD>
  <TD>[width]x[height]</TD>
</TR>
[EXIF-TAIL]
</TABLE>
</HTML>
```

Sample output from the above command and template run on a directory containing two files could be as follows:

```
<HTML>
<HEAD>My Photographs</HEAD>
<TABLE ID="Table1" BORDER=1 CELLSPACING=3 CELLPADDING=1 WIDTH=725>
<TR>
  <TD>File Name</TD>
  <TD>Date/Time</TD>
  <TD>File Size</TD>
  <TD>Dimensions</TD>
</TR>
<TR>
  <TD><a href="mydir/photo1.jpg">photo1.jpg</a></TD>
  <TD>2003:01:01 11:35:58</TD>
  <TD>65848</TD>
  <TD>1760x1168</TD>
</TR>
<TR>
  <TD><a href="mydir/photo2.jpg">photo2.jpg</a></TD>
  <TD>2003:01:01 11:40:00</TD>
  <TD>63458</TD>
  <TD>1760x1168</TD>
</TR>
</TABLE>
</HTML>
```

EXIFutils Command Reference

Example 4

You want to display one line per file, starting with the file name, a colon, then a list of fields separated by semicolon characters. A template to produce this out would look like this:

```
exiflist -o t -s "[file-name]: [make];[model];[shutter];[f-number]\n" .
```

Sample output from this command is:

```
photo1.jpg: NIKON;E995;1/125;2.8  
photo2.jpg: NIKON;E995;1/64;5.6  
photo3.jpg: NIKON;E995;1/125;2.8
```

7 Command Reference

7.1 EXIFCOPY

7.1.1 Description

In its simplest form the `exifcopy` command is used to copy Meta data (EXIF, IPTC, Flashpix) unmodified from one image file (the *source* file) to another image file (the *destination* file). For example:

```
exifcopy source.jpg dest.jpg
```

By default a backup copy of the destination file is kept. The name of the backup file will contain the suffix `-be` appended to the file name immediately before the `.` in the file name. For example, if the destination file name was `myphoto.jpg`, the backup file will be called `myphoto-be.jpg`. If you do not want a backup file, use the `-b` option.

If the destination file already contains Meta data, `exifcopy` will refuse to copy any Meta data. To force `exifcopy` to overwrite any Meta data in the destination file, use the `-o` option. This will cause any Meta data in the source file to overwrite Meta data in the destination file, IPTC data in the source file will replace IPTC data in the destination file, and Flashpix data in the source file will replace Flashpix data in the destination file. If a particular type of Meta data is not present in the source file, the corresponding data in the destination file will be left unchanged.

For example, if the `image1.jpg` contains only EXIF data and the `image2.jpg` contains only IPTC data, then the command:

```
exifcopy -o image1.jpg image2.jpg
```

will copy the EXIF data from `image1.jpg` into `image2.jpg`, and will leave the IPTC data in `image2.jpg` unchanged⁶.

7.1.1.1 Advanced Use

`exifcopy` can be used to copy Meta data (EXIF, IPTC, and Flashpix) between multiple image files in one command. This is achieved by specifying:

- o both the source and the destination as directory names
- o the source as a single file and the destination as a directory name

The selection of the source and destination files between which Meta data will be copied is controlled by the `-m` (match) option. The `-m` option specifies how many characters, counting from the left of the source file name, must be the same in the destination file name before copying will occur; if the file names match for the specified number of characters then the EXIF data will be copied between the files.

The `-m` option can be specified in two ways:

1. as the number of characters that must match (eg. `-m 8`)
2. as a dot (`-m .`) indicating that the files must match up to the first `.` in the source file name. For example, suppose the source file is `myphoto.jpg` and the possible destination files are `myphoto1.jpg` and `mypic.jpg`. Meta data will only be copied to `myphoto1.jpg` because there are seven characters before the `.` in the source file name, and `myphoto1.jpg` matches the source file name for the first seven characters.

⁶ If you want to separately delete EXIF, IPTC, or Flashpix information from an image file, use the `exifedit` command with the `/e` option. See Section 7.3 for more details.

EXIFutils Command Reference

If no `-m` option is specified then the file names must match exactly for the Meta data to be copied.

Specifying a match length of zero (`-m 0`) causes all source files to match all destination files. This is only useful when the source is a single file and the destination is a directory. In this scenario, specifying `-m 0` causes the EXIF data from the single source file to be copied into all the JPG files in the destination directory.

7.1.1.2 Supported Image File Types

For some file types it is possible to make an exact copy of all EXIF, IPTC, and Flashpix data from one file to another. For other file types only fields that can be edited⁷ by the EXIFutils can be copied between files.

Table 11 shows the image file types that support exact copying of all Meta data. Note that Minolta MRW files can only be the source file for an exact copy operation, not the destination file.

Table 11 File types for which exact copy is supported

File Type	Exact copying of all EXIF fields supported	Exact copying of all IPTC fields supported	Exact copying of all Flashpix data supported
JPEG	✓	✓	✓
TIF			
EXIF .EXI	✓	✓	✓
Canon .CRW			
Canon .CR2			
EPS			
Fujifilm .RAF			
Kodak .DCR			
Minolta .MRW	✓ (Note 1)		
Nikon .NEF			
EPS			

Note 1: An .MRW file can only be the *source* of the copied fields. Copying of field *into* an .MRW file is not supported

If both source and destination files support exact copies then by default an *exact* copy of *all* Meta data in the source file will be copied into the destination file. If the destination file already contains Meta data, `exifcopy` will not overwrite it unless the `-o` option (force overwrite) option is specified. If the `-f` option is specified then only the fields listed in the `-f` option will be copied (see below).

Performing an exact copy of all fields is not supported if the source file, destination file, or both do not support exact copying. In these cases only fields that EXIFutils considers to be editable⁸ can be copied⁹.

If you do not want to make an exact copy of all fields, or if exact copying is not supported for your file type, you can copy individual fields using the `-f` option. The `-f` option is used to specify a list of the nicknames of the fields to be copied, eg:

```
-f make,model,description,shutter
```

⁷ See Section 7.3.1.1 “Editable and non-Editable Fields” for an explanation of editable fields.

⁸ See EXIFutils Field Reference Guide for a list of fields that are editable.

⁹ You can force `exifcopy` to copy only selected fields between files that support exact copying by specifying the `/f` option.

EXIFutils Command Reference

If the `-f` is not specified then by default all `exif-common` and `iptc` fields are copied. See Section 3.1 “Selecting Multiple Fields” for a description of `exif-common` and `iptc`.

`exifcopy` does not check that the Meta data being copied is consistent with the image file into which it is being copied.

7.1.1.2.1 Canon Raw (.CRW) Files

Canon Raw .CRW files do not contain EXIF data; they contain Canon proprietary Meta data. If a .CRW files is the source of an `exifcopy` operation then the .CRW Meta data will be copied into the equivalent EXIF field in the destination file. If there is no equivalent EXIF field then the .CRW field is not copied. Table 12 shows the equivalent EXIF field for each .CRW field. Note that in some cases there is more than one EXIF field corresponding to a Canon .CRW field. In these cases the Canon field will be copied into all equivalent EXIF fields. For example, the Canon `crw-shutter` field value will be copied into both the `exp-time` and `shutter` EXIF fields.

A Canon .CRW file cannot be the destination of an `exifcopy` operation.

Table 12 Canon .CRW to EXIF Field Translations

Canon .CRW Field	Equivalent EXIF Field	Description
<code>crw-vendor</code>	<code>make</code>	Camera Make
<code>crw-model</code>	<code>model</code>	Camera Model
<code>crw-date</code>	<code>date-taken</code>	Date Taken
<code>crw-firm-ver</code>	<code>firm-ver</code>	Firmware Version
<code>crw-iso</code>	<code>iso-speed</code>	ISO Speed Setting
<code>crw-exp-comp</code>	<code>exp-bias</code>	Exposure Compensation
<code>crw-shutter</code>	<code>shutter</code>	Shutter Speed
	<code>exp-time</code>	Exposure Time
<code>crw-aperture</code>	<code>aperture</code>	Aperture
	<code>f-number</code>	F-number

7.1.2 Command Syntax

```
exifcopy [-b] [-o] [-q] [-f field-list] \
          [-p cmd=charset,exif=charset,iptc=charset] \
          src-file dest-file
```

```
exifcopy [-b] [-c] [-I] [-o] [-q] [-f field-list] \
          [-p cmd=charset,exif=charset,iptc=charset] \
          src-file dest-directory
```

```
exifcopy [-b] [-c] [-I] [-o] [-q] [-f field-list] \
          [-p cmd=charset,exif=charset,iptc=charset] \
          src-directory dest-directory
```

```
exifcopy [-v|-h]
```

`-b` Do not save a backup copy of the original destination file(s).

`-c` File name comparisons are to be case-sensitive (this is the default on Linux, MacOS X, and Solaris).

`-f field-list`
Copy only the fields specified in *field-list* from the source to the destination file(s).

EXIFutils Command Reference

- h Display `exifcopy` usage information
- i File name comparisons are to be case-insensitive (this is the default on Windows)
- m [`.|n`] Specifies the number of characters that must match between the source file name and destination file name before Meta data will be copied. '`-m .`' specifies that the file names must match up to the position of the first '`.`' in the source file name.
- o Force overwriting of EXIF data in the destination file.
- p [`cmd=xxx`], [`exif=xxx`], [`iptc=xxx`]
Specify the character sets to be used when interpreting/displaying text fields
 - `cmd=xxx` sets the charset to be used for output displayed from this command.
 - `exif=xxx` sets the charset to be used for reading/writing EXIF text fields
 - `iptc=xxx` sets the charset to be used for reading/writing IPTC text fields

Any of the three may be omitted. For example:

```
-p exif=latin1,iptc=mac  
-p cmd=utf8
```

These values can also be set using the `EXIFUTILS_CS_CMD`, `EXIFUTILS_CS_EXIF`, `EXIFUTILS_CS_IPTC` environment variables.

See Section 5 “Character Sets” for more information.
- q Quiet mode. Do not display warning messages.
- v Display program version information. This is the default action if no other options are present.

7.1.3 Examples

```
exifcopy Dcp_0123.jpg Dcp_0123_new.jpg
```

Takes an exact copy of all Meta data (EXIF, IPTC, Flashpix) from `Dcp_0123.jpg` and copies it into `Dcp_0123_new.jpg`. An unaltered copy of `Dcp_0123_new.jpg` will be left in the current directory with the name `Dcp_0123_new-be.jpg`. If `Dcp_0123_new.jpg` already contains Meta data then an error will be displayed and `Dcp_0123_new.jpg` will be left unaltered.

```
exifcopy -o -b Dcp_0123.jpg Dcp_0123_new.jpg
```

Copies the Meta information from `Dcp_0123.jpg` into `Dcp_0123_new.jpg`. If `Dcp_0123_new.jpg` already contains Meta information then it will be overwritten (`-o` option). No backup copy of `Dcp_0123_new.jpg` will be kept (`-b` option).

```
exifcopy -f date-taken,f-number,ip-caption Dcp_0123.jpg Dcp_0123.tiff
```

EXIFutils Command Reference

Copies the `date-taken` and `f-number` EXIF fields, and the `ip-caption` IPTC field from `Dcp_0123.jpg` into `Dcp_0123.tiff`. If `Dcp_0123.tiff` already contains any of these fields then they will be overwritten. An unaltered copy of `Dcp_0123.tiff` will be left in the current directory with the name `Dcp_0123-be.tiff`.

```
exifcopy PICT0123.mrw PICT0123.jpg
```

Takes an exact copy of all Meta information from `Dcp_0123.mrw` and copies it into `Dcp_0123.jpg`. An unaltered copy of `Dcp_0123.jpg` will be left in the current directory with the name `Dcp_0123-be.jpg`. If `Dcp_0123.jpg` already contains Meta information then an error will be displayed and `Dcp_0123.jpg` will be left unaltered.

7.2 EXIFDATE

7.2.1 Description

The `exifdate` command modifies all EXIF date/time fields in the specified image files. If the specified file is a directory then the date fields in all image files in that directory will be modified.

The way in which the date is modified is governed by the action parameter. Valid actions are:

- Add (`-a`) the specified date/time value will be *added* to every EXIF date/time field
- Subtract (`-s`) the specified date/time value will be *subtracted* from every EXIF date/time field
- Replace *replace* some or all of the EXIF date/time with a specific value. This is the default action if neither `-a` or `-s` is specified.

The value to *add to*, *subtract from*, or *replace with* is specified by the date/time parameter.

The format of the date/time parameter is:

```
yyyy:mm:dd hh:mm:ss
```

Note that when a full date/time is specified on the command line, quote characters must surround it. For example,

```
exifdate "2001:03:16 12:23:00" image.jpg
```

The quotes are required because the date/time contains an embedded blank.

Either the date or time portion can be omitted, so both of the following formats are also valid:

```
yyyy:mm:dd      eg. 2001:03:16  
hh:mm:ss       eg. 01:00:00
```

If the action is *Replace*, any portion of the date or time can be replaced with x's to indicate that part of the field is not to be replaced. For example, in the command

```
exifdate 1999:xx:xx image.jpg
```

the date parameter indicates that the year field is to be set to 1999, but the month and day are to be left unchanged. The time will also be left unchanged because the time part of the date/time was not specified.

EXIFutils Command Reference

7.2.1.1 Supported Image File Types

Table 13 shows the files types that are supported by `exifdate`.

Table 13 File Types Support by `exifdate`

File Type	Supported by <code>exifdate</code>
JPEG	✓
TIF	✓
EXIF .EXI	✓
Canon .CRW	
Canon .CR2	✓
EPS	
Fujifilm .RAF	✓
Kodak .DCR	✓
Minolta .MRW	✓
Nikon .NEF	✓

7.2.2 Command Syntax

```
exifdate -a [-q] [-r] date-time file,... directory,...
exifdate -s [-q] [-r] date-time file,... directory,...
exifdate [-q] [-r] date-time file,... directory,...
exifdate [-h|-v]
```

- a Add *date-time* to all EXIF date fields in the specified image files.
- h Display `exifdate` usage information.
- q Quiet mode. Do not display warning messages.
- r Include subdirectories. If any directories are specified, then dates in all image files in the specified directory and all of its subdirectories will be modified.
- s Subtract *date-time* from all EXIF date fields in the specified image files.
- v Display program version information. This is the default action if no other options are present.

7.2.3 Examples

```
exifdate "1999:06:01 14:27:08" image1.jpg image2.jpg
```

Set the date fields in `image1.jpg` and `image2.jpg` to 1999:06:01 14:27:08

```
exifdate "xxxx:06:xx" my-dir1 mydir2
```

Change the month to 06 in all date fields in image files in the directories `my-dir1` and `mydir2`.

```
exifdate -a "0001:03:05" image.jpg
```

EXIFutils Command Reference

Add 1 year, 3 months, and 5 days to all date/time fields in `image.jpg`.

```
exifdate -a "01:30:00" image.jpg
```

Add 1 hour and 30 minutes to all date/time fields in `image.jpg`.

```
exifdate -r -s "12:00:00" my-dir
```

Subtract 12 hours from the date/time fields of all image files in directory `my-dir` and all of its subdirectories (`-r` option).

7.3 EXIFEDIT

7.3.1 Description

The `exifedit` command adds, modifies, and deletes EXIF and IPTC fields from image files. The edit action to be performed is specified by one or more of the following command line options:

- a Add one or more EXIF or IPTC fields. The fields to be added, and their values, are specified in a field value list following the `-a` option. Fields already existing in the image file will have their value replaced with the specified value. See Section 7.3.1.2.
- r Remove one or more EXIF or IPTC fields. The fields to be removed are specified as a field list following the `-r` option. See Section 7.3.1.3.
- s Update the EXIF `width` and `height` fields to match actual image values (JPEG files only). See Section 7.3.1.4.
- t Remove or update EXIF thumbnail image. See Section 7.3.1.4.
- e Erase all EXIF, IPTC, and/or Flashpix information from the file (JPEG and .EXI files only). See Section 7.3.1.5.

By default a copy of the original (unedited) image file will be saved with a `'-be'` suffix. For example, if you edit the file `myphoto.jpg` then a backup will be saved with the name `myphoto-be.jpg`. Use the `-b` option if you do not want the backup file created.

7.3.1.1 Editable and non-Editable Fields

Editable fields are fields for which EXIFutils can change the value. EXIFutils does not allow the user to edit all EXIF and IPTC fields for one or more of the following reasons:

1. The value of some fields must be generated by EXIFutils to ensure correct formatting of the EXIF and IPTC data structures.
2. EXIFutils does not yet support formatting of the data type in which the field is stored.
3. The field is a non-standard field that EXIFutils does not know how to correctly format. This is most often the case with Maker Note fields, which are defined by each camera manufacturers and for which the correct format definitions are not published.

A complete list of all fields, with an indication of whether they are editable by EXIFutils is available in Section 8 and the EXIFutils Field Reference Guide.

7.3.1.2 Adding Individual EXIF and IPTC Fields (`-a` option)

The `exifedit -a` option is used to add EXIF and IPTC fields to an image file. To use `exifedit` you need to know the nickname of the field you want to add, and the value to which you want to set it. See EXIFutils Getting Started Guide for an explanation of how to find the nickname of a field.

Once you know the nickname and the value you want to set, enter the following command:

```
exifedit -a nickname=value file-name
```

For example, if you want to add the shutter speed field (nickname `shutter`) with a value of `1/125` to `myphoto.jpg`, enter the following command:

```
exifedit -a shutter=1/125 myphoto.jpg
```

Note that if the field value contains a space character, or if you include one or more spaces before or after the `"="`, then the whole `nickname=value` string must be surrounded by quotes, eg:

```
exifedit -a "date-taken=2004:01:01 23:59:59" myphoto.jpg
```

EXIFutils Command Reference

Also, if the field value contains a comma or a semicolon, then it is necessary to put quotes¹⁰ around both the field value and the whole nickname=value string. To do this you must escape the embedded quote characters¹¹:

```
exifedit -a "comment=\"I took this, for sure\"" myphoto.jpg
```

To set multiple EXIF and/or IPTC fields in one command, you can specify multiple nickname/value pairs in the `-a` option, separated by commas, i.e.

```
exifedit -a nickname=value,nickname=value,nickname=value file-name
```

As before if there are spaces anywhere in the nickname=value string, or if a field value contains a comma or a space, then the whole string must be surrounded by quotes, eg:

```
exifedit -a "shutter=1/125, comment=\"I took this, for sure\"" myphoto.jpg
```

7.3.1.2.1 Adding Repeating IPTC Fields

All EXIF fields and most IPTC fields can only appear once in an image file. For example, you can only put one EXIF `description` field in an image. If you add a description field when one is already present, EXIFutils will delete the existing `description` field and replace it with the new description.

Some IPTC fields can occur more than one, for example the Keyword field (nickname `ip-keyword`) and Supplementary Category field (nickname `ip-suppcat`). Repeating IPTC fields can appear up to 999¹² times within an image file. See the EXIFutils Field Reference Guide for information about which IPTC fields can be present more than once.

Each time a repeating field is added to a file, a new instance of that field is added to the file. For example, if you run the following two commands one after the other, there will be two `ip-keyword` fields in the file:

```
exifedit -a ip-keyword=sports myfile.jpg
exifedit -a ip-keyword=soccer myfile.jpg
```

When you display a repeating field with `exiflist`, it will display all of the instances that are in the file. For example:

```
>exiflist -o ln -f ip-keyword myfile.jpg
ip-keyword="sport; soccer"
```

You can add multiple repeating values in one command by using one of the following formats:

```
exifedit -a ip-keyword=sports,ip-keyword=soccer myfile.jpg
exifedit -a "ip-keyword=sports;soccer" myfile.jpg
```

These two commands have exactly the same result, and each is equivalent to the two commands shown in the initial `exifedit` example above.

¹⁰ See also the `exifedit /c` option, which can be used to change the quote character used when quoting `exifedit` field values.

¹¹ The examples given in this section apply to the Windows version of EXIFutils and to the OSX, Linux, and Solaris versions of the product when used with a Bourne-based command shell. The method used to embed quotes when using other command shells may be different.

¹² The limit of 999 repetitions is imposed by EXIFutils. According to the IPTC specification the number of times a field can be repeated is limited only by available memory.

EXIFutils Command Reference

By default, a semicolon is used to separate multiple repeating field values. You can change this separator character using the `-j` option.

7.3.1.2.2 Setting Field Values Using the Value of Other Fields

Using *template* values, you can set fields using the values of other fields. For example, if you have a description of a photo in the EXIF `description` field, and you want to copy this value into the IPTC `ip-caption` field, you can do the following:

```
exifedit -a "ip-caption=[description]" myfile.jpg
```

You can also combine multiple fields into one value, for example:

```
exifedit -a "ip-caption=Photo taken at [date-taken], F-stop [f-number]" myfile.jpg
```

See also Section 4.4 “Converting Between EXIF and IPTC Date/Time Formats” for more information on setting EXIF date/time fields based on IPTC date/time values, and vice versa.

7.3.1.3 Removing Individual EXIF or IPTC fields (`-r` option)

The `exifedit -r` option is used to remove individual EXIF and IPTC fields from an image file. To do this you need to know the nickname of the field you want to remove. See EXIFutils Getting Started Guide for an explanation of how to find the nickname of a field.

Once you know the nickname of the field(s) you want to remove, enter the following command:

```
exifedit -r nickname,nickname,nickname file-name
```

For example, to remove the EXIF description field, and the IPTC caption field, enter the following command:

```
exifedit -r description,ip-caption myfile.jpg
```

To remove all EXIF and/or IPTC fields, see Section 7.3.1.5 “Erasing all Meta data (`-e` option)”

7.3.1.3.1 Removing Repeating IPTC Fields

As explained in Section 7.3.1.2.1, some IPTC fields can be present multiple times in an image file. If you remove either of these fields using the `exifedit -r` option, all occurrence of the field will be removed.

For example, if the file `myfile.jpg` contains two occurrences of the `ip-keyword` field added by the command:

```
exifedit -a "ip-keyword=planes,ip-keyword=planes" myfile.jpg
```

then the following command will delete both occurrences of the `ip-keyword` field:

```
exifedit -r ip-keyword myfile.jpg
```

EXIFutils do not provide the option to delete individual occurrences of a repeating IPTC field.

7.3.1.4 Updating EXIF fields to match the actual image (`-s` and `-t` options)

Many photo editing programs do not update the EXIF image information when you save an image after editing it. EXIFutils provides the `exifedit -s` and `-t` options update the EXIF fields.

EXIFutils Command Reference

The `-s` option is used to set the EXIF image `width` and `height` values to the actual size of the main image. The `-t` option is used update the EXIF thumbnail image to match the main image. The `-s` and `-t` options can be used either together or separately.

For example:

```
exifedit -s myfile.jpg
```

```
exifedit -t a myfile.jpg
```

```
exifedit -s -t a myfile.jpg
```

The `exifedit -t a` option creates a thumbnail with the default dimensions of 160x120. See Section 7.3.2 for details of how to change the size of the generated thumbnail.

7.3.1.5 Erasing all Meta data (-e option)

The `exifedit -e` option is used to delete all Meta data from a JPEG image file. It can also be used to selectively remove only EXIF Meta data, IPTC Meta data, or Flashpix Meta data from a JPEG file.

To delete all Meta data (EXIF, IPTC, and Flashpix) use the `'-e a'` option. For example:

```
exifedit -e a myfile.jpg
```

To delete all EXIF Meta data, but leave IPTC and Flashpix Meta data, using the `'-e e'` option. For example:

```
exifedit -e e myfile.jpg
```

To delete all IPTC Meta data, but leave EXIF and Flashpix Meta data, using the `'-e i'` option. For example:

```
exifedit -e i myfile.jpg
```

To delete all Flashpix Meta data, but leave EXIF and IPTC Meta data, using the `'-e f'` option. For example:

```
exifedit -e f myfile.jpg
```

Deletion of Ricoh RMETA Meta data is not supported.

7.3.1.6 Supported Image File Types

Table 14 shows the image file types supported by `exifedit`.

Table 14 Image File Types Supported by `exifedit`

File Type	-e option	-s option	All other options
JPEG	✓	✓	✓
EXIF .EXI	✓		✓
TIF			✓
Canon .CR2			✓
Kodak .DCR			✓
Nikon .NEF			✓
Canon .CRW			
Fujifilm .RAF			

EXIFutils Command Reference

Minolta .MRW			
EPS			

7.3.2 Command Syntax

```
exifedit [-b] [-q] [-i] [-s] [-u] [-c x] [-j x] \  
          [-p cmd=charset,exif=charset,iptc=charset] \  
          [-a field-value-list|@filename] \  
          [-r field-list] \  
          [-t [r|a|a,size|a,wwwxhhh|a,@filename]] file...  
exifedit [-b] [-q] [-i] -e [a|e|f|i] file...  
exifedit [-h|-v]
```

`-a [field-value-list | @file-name | @-]`

Add the specified field(s) to the image file(s). The *field-value-list* is specified as a comma separated list of field nickname/value pairs in the following format:

```
-a fieldname=fieldvalue,fieldname=fieldvalue
```

For example:

```
-a "description=I took this,shutter=1/125,f-number=2.8"
```

The *fieldvalue* can also be specified as a template. See Section 6 “Templates” for more details.

Alternatively, the name of a file containing the *field-value-list* in the above format can be specified. For example:

```
-a @my-field-values.txt
```

The file name can also be specified as ‘-’ which indicates that the *field-value-list* will be read from stdin. For example:

```
-a @-
```

`-b` Do not keep a backup copy of the original unedited image file(s).

`-c x` Specifies the character to be used as the quote character in the field value list. ‘x’ can be any printable character except “ or \. For example

```
-c : -a "description=:My birthday, last year:"
```

sets the quote character to the colon character and uses it to delimit the text value of the description field.

`-e [a|e|f|i]`

Erase Meta data from the file. The types of Meta data to be removed are specified by the sub-parameter:

`-e a` Erase all EXIF, IPTC, and Flaspix Meta data.

`-e e` Erase all EXIF data. All APP1 data blocks will be removed.

`-e f` Erase all Flaspix data. All APP2 FlashPix data blocks will be removed.

EXIFutils Command Reference

`-e i` Erase all IPTC data. All APP13 data blocks will be removed.

This option is only valid for JPEG files. It has no effect on other file types. This option cannot be specified with the `-a`, `-r`, `-t`, or `-s` options.

`-h` Display `exifedit` usage information.

`-i` Recursive mode. If any of the files specified is a directory, then image files in the specified directory and all of its subdirectories will be processed.

CAUTION SHOULD BE TAKEN WHEN USING THIS OPTION AS IT CAN POTENTIALLY MODIFY A LARGE NUMBER OF FILES.

`-j [x|0xnn|0nnn]`

Specify the field separator character to be used to separate repeating IPTC fields in the `-a` option. This can be specified in one of three ways:

- o As a printable character, for example `-j +`
- o As a hexadecimal value, for example `-j 0x10`
- o As an octal value with a leading zero, for example `-j 020`

The default value is a semicolon `;`

`-p [cmd=xxx], [exif=xxx], [iptc=xxx]`

Specify the character sets to be used when interpreting/displaying text fields

- `cmd=xxx` sets the charset to be used for output displayed from this command.
- `exif=xxx` sets the charset to be used for reading/writing EXIF text fields
- `iptc=xxx` sets the charset to be used for reading/writing IPTC text fields

Any of the three may be omitted. For example:

```
-p exif=latin1,iptc=mac
-p cmd=utf8
```

These values can also be set using the `EXIFUTILS_CS_CMD`, `EXIFUTILS_CS_EXIF`, `EXIFUTILS_CS_IPTC` environment variables.

See Section 5 “Character Sets” for more information.

`-q` Quiet mode. Do not display warning messages

`-r field-list`

Remove the specified EXIF and/or IPTC fields. If a repeating IPTC field is specified (`ip-keyword` or `ip-suppcat`) then all occurrences of that field will be deleted. The field list is specified as a comma separated list of field nicknames in the following format:

```
-r fieldname,fieldname,fieldname,fieldname
```

For example:

```
-r description,shutter,f-number,comment
```

Alternatively, the name of a file containing the `field-list` in the above format can be specified. For example:

```
-r @my-field-list.txt
```

EXIFutils Command Reference

The file name can also be specified as dash '-' which indicates that the *field-list* should be read from stdin. For example:

```
-r @-
```

-s Set the EXIF *width* and *height* fields for the main image to match the actual width and height of the main JPEG image.

This option can only be used on JPEG files. It has no effect on other file types.

-t [*a*|*a,size*|*a,wxhh*|*a,@filename*|*r*]

The '-t a' option replaces an existing thumbnail image (if any) with either a thumbnail provided by the user, or one generated from the main JPEG image by *exifedit*. If a thumbnail is to be generated, the size of the generated thumbnail image can be specified in one of three ways:

-t a The generated thumbnail will be the default size 160 pixels wide by 120 pixels high. This size conforms to the DCF V1.0 specification and therefore many digital cameras and image processing programs expect the thumbnail to be this size.

-t *a,size* The specified *size* is the size (in pixels) of the longest dimension of the thumbnail image. The size of the other dimension will be scaled to maintain the aspect ratio of the image. For example, if you specified -t *a,100* and the size of the main image is 1000x500, then the thumbnail dimensions will be 100x50. Using the same thumbnail specification -t *a,100* with a main image size of 500x1000, then the thumbnail dimensions will be 50x100.

-t *a,wxhh* The thumbnail dimensions will be *ww* pixels wide by *hh* pixels high, eg
-t *a,200x100*

If the thumbnail is to be replaced with a JPEG image provided by the user, then it is specified as follows:

-t *a,@filename*

The thumbnail will be replaced with the image in the specified *filename*. The specified thumbnail file must be in the same directory as the image file, and is checked to ensure that it is a JPEG file.

The -t *r* option removes any existing EXIF thumbnail image and all thumbnail related EXIF fields.

The -t option can only be used on JPEG files. It has no effect on other file types.

-u Store EXIF *comment* field as UNICODE (default is ASCII). See Section 5.3 "EXIF Comment Field" for more information.

-v Display program version information. This is the default action if no other options are present.

7.3.3 Examples

EXIFutils Command Reference

```
exifedit -a "copyright=Copyright (c) 2001 John Citizen" my-dir
```

Add the `copyright` field to all image files in the directory `my-dir`. If the `copyright` field is already present in any of the files, it will be replaced with the value specified. A backup copy of all edited files will be created.

```
exifedit -r comment,description,ip-keyword myfile.jpg
```

Removes the `comment`, `description`, and all instances of the `ip-keyword` field from `myfile.jpg`.

```
exifedit -t r mydir fred.jpg
```

Removes the thumbnail images and EXIF Thumbnail fields from all the JPEG files in the directory `mydir`, and from the file `fred.jpg` in the current directory.

```
exifedit -t a,@fred-thumb.jpg mydir fred.jpg
```

Replaces the thumbnail image in `fred.jpg` with the image in `fred-thumb.jpg`.

```
exifedit -c : -a "comment=:my photo:" -t a -r copyright mydir
```

Performs the following changes to all JPEGs in the `mydir` directory:

- o adds the `comment` field with the value 'my photo' (`-a` option)
- o replaces any existing EXIF thumbnail image with a new thumbnail based on the main JPEG image. (`-t` option)
- o removes the `copyright` field (`-r` option)

An alternative quote character ':' is used (`-c` option).

```
exifedit -a @fields.txt myfile.jpg
```

Adds the fields/values specified in the file `fields.txt` (located in the current directory) into the JPEG file `myfile.jpg`

Sample contents of `fields.txt` is show below:

```
copyright="Copyright (c) Jane Citizen.",
description="Loch Ness in winter",
comment="This is a photo I look of Loch Ness in winter.
The comment spans more than one line, but that is OK
because exifedit will replace each new line character
with a space."
```

```
exifedit -a "comment=Taken at [date-taken] by [ip-byline]" myfile.jpg
```

Adds the `comment` field to `myfile.jpg`. The value of the `comment` field is generated using a supplied substitution template. If the `date-taken` field has a value of '2000:12:31 23:59:59' and the `ip-byline` field has value of "Jane Smith", then in the above example the `comment` field will be set to:

```
"Taken at 2000:12:31 23:59:59 by Jane Smith".
```

```
exifedit -a "ip-headline=Joe Triumphs,ip-keyword=sport,keyword=olympics" myfile.jpg
```

Adds the IPTC `ip-headline` field, and two instances of the IPTC `ip-keyword` field to `myfile.jpg`.

7.4 EXIFFILE

7.4.1 Description

The `exiffile` command is used to change the attributes of an image file based on the value of EXIF, IPTC, and RMETA fields. The operation to be performed by `exiffile` is selected by one of the following command line options:

- n Rename one or more image files based on field values
- t Change the “last modified” timestamp of one or more images files to match the date/time that each image was taken.

Both the `-n` and `-t` options can be specified on the same command.

7.4.1.1 Renaming Files

`exiffile` renames image files based on a file name *template* specified in the `-n` option. A template is a text string containing markers indicating where field values are to be substituted. A marker consists of an EXIFutils field nickname surrounded by square brackets “[]”. For example, if you wanted to rename an image file so that the file name was the same as the date/time the image was taken, then you would use the following command:

```
exiffile -n “[date-taken].jpg” myphoto.jpg
```

You can use any EXIFutils field nickname in the template. See Section 8 for a complete list of nicknames. Templates are described in more detail in Section 6 “Templates”.

To ensure that the resulting file name is valid, `exiffile` will replace any illegal characters with a dash “-”. You can change this substitution character to a different character using the `-c` option. The only character that is illegal in a file name is ‘/’

If you specify the `-s` option, `exiffile` will also replace any space characters in the file name with the substitution character.

7.4.1.1.1 File Name Clashes

When attempting to rename a file, `exiffile` first checks to see if a file with that name already exists. If it does, then `exiffile` will add a suffix to the name to ensure that the name is unique. The suffix is a number surrounded by brackets, eg “(1)”. For example, if a file is to be renamed to “2004-01-01-12-23-23.jpg”, but a file with that name already exists, `exiffile` will rename the file to “2004-01-01-12-23-23(1).jpg”. If that file name also exists, `exiffile` will attempt to rename it to “2004-01-01-12-23-23(2).jpg”, and so on.

7.4.1.2 Changing the “Last Modified” Date

When the `-t` option is specified `exiffile` will, for each image, attempt to set the last modified date of the file to be the same as the value of the `date-taken` field. If the `date-taken` field is not present in the image file then the last modified timestamp will be set to the value of the `date-digi` (date digitised) field. If the `date-digi` field is not present in the image file then the last modified timestamp will be set to the value of the `date-mod` (date modified) field.

If none of the above date fields is present in the image file then an error is displayed and no change is made to the last modified date of the file.

Note: `exiffile` attempts to adjust for Daylight Saving Time (DST). To do so `exiffile` relies on the underlying settings and services provided by the operating system. Correct Daylight Saving/Summer time conversion relies on these system settings being correct.

EXIFutils Command Reference

7.4.1.3 Supported Image File Types

Table 15 shows the image file types supported by `exiffile`.

Table 15 Image File Type Supported by `exiffile`

File Type	-n option	-t option
JPEG	✓	✓
EXIF .EXI	✓	✓
TIF	✓	✓
Canon .CR2	✓	✓
Canon .CRW	✓	
EPS	✓	✓
Fujifilm .RAF	✓	✓
Minolta .MRW	✓	✓
Kodak .DCR	✓	✓
Nikon .NEF	✓	✓
EPS	✓	✓

7.4.2 Command Syntax

```
exiffile [-q] [-r] [-t] [-c x] [-s] [-p cmd=charset,exif=charset,iptc=charset] \  
          [-n file-name-template|@filename|@-] file...  
exiffile [-h|-v]
```

`-c x` Sets the character to be used to replace illegal characters (and optionally space characters – see `-s` option) in file names. If `-c` is not specified then by default the dash character “-” will be used. This option is ignored if the `-n` option is not also specified.

`-h` Display `exiffile` usage information.

`-n [file-name-template | @filename | @-]`

Rename the image file to the name specified by `file-name-template`. See Section 6 “Templates” for more information about templates. This option can be specified in one of three ways:

- 1) on the command line, for example:

```
-n [date-taken]-[model].jpg
```

- 2) as an ampersand followed by the name of a text file containing the `file-name-template`:

```
-n @template.txt
```

- 3) an ampersand followed by a ‘-’, indicating that the `file-name-template` is to be read from stdin, for example:

```
-n @-
```

After substitution of field values in to the `file-name-template` is complete, any characters that are invalid in a file name will be replaced with the substitution character (see `-c` option). If `-s` has been specified, any spaces in the file name will also be replaced with the substitution character.

EXIFutils Command Reference

`-p [cmd=xxx], [exif=xxx], [iptc=xxx]`

Specify the character sets to be used when interpreting/displaying text fields

`cmd=xxx` sets the charset to be used for output displayed by this command.
`exif=xxx` sets the charset to be used for reading EXIF text fields
`iptc=xxx` sets the charset to be used for reading IPTC text fields

Any of the three may be omitted. For example:

```
-p exif=latin1,iptc=mac
-p cmd=utf8
```

These values can also be set using the `EXIFUTILS_CS_CMD`, `EXIFUTILS_CS_EXIF`, `EXIFUTILS_CS_IPTC` environment variables.

See Section 5 “Character Sets” for more information.

- `-q` Quiet mode. Do not display warning messages.
- `-r` Recursive mode. If any of the files specified is a directory, then image files in the specified directory and all of its subdirectories will be processed.
- `-s` Replace spaces. Any spaces in the file name specified in the `-n` option will be replaced with the substitution character (see `-c` option). This option is ignored if the `-n` option is not also specified.
- `-t` Set last modified timestamp of the image file to match the value in the `date-taken` EXIF field.
- `-v` Display program version and licensing information. This is the default action if no other options are present.

7.4.3 Examples

```
exiffile -t myimage.jpg
```

Sets the last modified timestamp of the image file `myimage.jpg` to the value of the `date-taken` field.

```
exiffile -t -r .
```

Sets the last modified timestamp of all image files in the current directory and any subdirectories of the current directory to the value of the `date-taken` field.

```
exiffile -n [date-taken]-[description].jpg myphoto.jpg
```

Renames `myphoto.jpg` to the name resulting from the substitution of the `date-taken` and `description` EXIF fields. For example, if `date-taken` has a value of “2002:12:31 23:59:59”, and the `description` field has a value of “New Years Eve Party”, then `myphoto.jpg` will be renamed to:

```
2002:12:31 23:59:59-New Years Eve Party.jpg
```

EXIFutils Command Reference

```
exiffile -c _ -s -n [date-taken]-[description].jpg myphoto.jpg
```

Rename `myphoto.jpg` to the name resulting from the substitution of the `date-taken` and `description` EXIF fields in the `file-name-template`. Any characters that are illegal in a file name will be replaced with an underscore (`-c _` option). Any spaces will also be replaced with an underscore (`-s` option). For example, if `date-taken` has a value of “2002:12:31 23:59:59”, and the `description` field has a value of “New Years Eve Party”, then `myphoto.jpg` will be renamed to:

```
2002_12_31_23_59_59-New_Years_Eve_Party.jpg
```

7.5 EXIFKEY

7.5.1 Description

The `exifkey` command installs the license key used to enable the full functionality of the EXIFutils. It is also used to display a license that has already been installed.

When you purchase a registered version of EXIFutils you will be provided with a 13-digit license key. This key is generated based on the user name and email address you supplied when you purchased EXIFutils from REG.NET. This key, and the username and email address you supplied, must be installed in the EXIFutils license file on your system in order to use the full EXIFutils functionality.

If no license key is installed, or if the license key installed is invalid, the following restrictions are imposed on the operation of the EXIFutils:

- o no more than 10 image files can be processed in a single invocation of any EXIFutils command,
- o no more than 5 field names can be specified in a field list or field value list,
- o only the first 2 fields in a template will be substituted. Subsequent fields will be replaced with the word "Demo"
- o for repeating IPTC fields, only the first 2 instances of the field will be displayed. Subsequent instances will be replaced with the word "Demo".
- o only the first 50 characters in IPTC field values will be displayed
- o in `exifedit`, the maximum length that a string field value can be set to is 99 characters (if a valid license is installed string values can be up to 999 characters),
- o in `exifedit`, only one action parameter can be specified in a single invocation of the command, i.e. you specify one and only one of the following parameters: `-a`, `-e`, `-r`, `-s`, or `-t`.

To install your license key use `exifkey` as shown:

```
exifkey -k licensekey -u "username" -e emailaddr
```

where

- o `licensekey` is the license key you received when you purchased your EXIFutils license
- o `username` is the user name exactly as you entered it when you purchased EXIFutils
- o `emailaddr` is the email address exactly as you entered it when you purchased EXIFutils

For example, if the username you supplied when you purchased the EXIFutils was Jane Smith, the email address was `jane@smith.com`, and the license key you were provide was `1234567890123`, then you would enter the `exifkey` command:

```
exifkey -k 1234567890123 -u "Jane Smith" -e jane@smith.com
```

Note that the user name and email address must be entered EXACTLY as specified when you purchased EXIFutils. If the above command correctly installs the license, then the following command would **not** correctly install the license:

```
exifkey -k 1234567890123 -u "jane smith" -e jane@smith.com
```

The above command would not correctly install the license because the user name has been entered as all lower case characters, whereas the first character of each name was upper case when the EXIFutils were purchased.

To display the installed license, use the `-l` option:

```
exifkey -l
```

EXIFutils Command Reference

7.5.2 Command Syntax

```
exifkey -k licensekey -u username -k emailaddr  
exifkey [-h|-v|-l]
```

- e *emailaddr*
Email address supplied when the license key was purchased
- h
Display `exifkey` usage information
- k *licensekey*
13 digit EXIFutils license key
- l
List details of the installed license
- u *username*
User name supplied when the license key was purchased
- v
Display program version and licensing information. This is the default action if no other options are present.

7.5.3 Examples

```
exifkey -l
```

List details of the currently installed license. Sample output is included below:

```
License Key           : 7721245622797  
Licensed User        : Jane Citizen  
Licensed Email Address : jane@citizen.com  
Licensed Operating System : Any  
Installed EXIFutils Version: 2.x  
License Status       : License Valid
```

If this installed license is not valid then a message similar to the following will be displayed:

```
*** License key is not correct for this user or product version. ***  
*** Check that all details have been entered correctly.           ***
```

```
License Key           : 9999999999999  
Licensed User Name    : Jane Citizen  
Licensed Email Address: jane@citizen.com  
Licensed Version      : 2.x  
License Status       : Invalid
```

7.6 EXIFLIST

7.6.1 Description

The primary function of the `exiflist` command is to extract EXIF, IPTC, and RMETA field values from one or more image files, and display them in the format selected via the command parameters. The default action if no command option is specified is to display all fields.

In addition, `exiflist` is used to:

- extract a copy of the thumbnail image from the EXIF data and write it to a separate JPEG file (`-t` option). See Section 7.6.3.
- extract a copy of the audio stream from the EXIF data and write it to a separate .WAV file (`-w` option). See Section 7.6.5.
- Extract an exact copy of all Meta data (EXIF, IPTC, and Flashpix) into a separate .EXI file (`-e` option). See Section 7.6.4.
- list attribute information about the EXIF and IPTC fields that are supported by the EXIFutils, including their format, and the valid values to which they can be set (`-l` option). See Section 7.6.6.
- list the character sets that will be used by `exiflist` to interpret EXIF and IPTC text fields (`-i` option). See Section 7.6.7.

7.6.1.1 Supported Image File Types

Not all `exiflist` features can be used with all image file types. Table 16 shows the features that are supported for each image file type.

Table 16 File Types for which `exiflist` Options are Supported

File Type	No options (list all fields)	Field List (<code>-o</code> option)	EXIF Block Extraction (<code>-e</code> option)	Thumbnail Extraction (<code>-t</code> option)	Audio File Extraction (<code>-w</code> option)
JPEG	✓	✓	✓	✓	✓
TIF	✓	✓			
EXIF .EXI	✓	✓	✓	✓	
Canon .CR2	✓	✓			
Canon .CRW	✓	✓			
Fujifilm .RAF	✓	✓		✓	
Kodak .DCR	✓	✓			
Minolta .MRW	✓	✓	✓	✓	
Nikon .NEF	✓	✓			
EPS	✓	✓			

EXIFutils Command Reference

7.6.2 Output Format Options

`exiflist` provides four types of display formats, selected by the `-o` option:

Format Type	Command Options	Description
Full field display	<code>-o a</code> <code>-o e</code> <code>-o i</code> <code>-o r</code>	Displays full details of all EXIF fields (<code>-o e</code>), all IPTC fields (<code>-o i</code>), all RMETA fields (<code>-o r</code>) or all fields (<code>-o a</code>). See Section 7.6.2.1.
Field list	<code>-o l</code> <code>-o lh</code> <code>-o ln</code> <code>-o lf</code>	Displays selected fields as a comma (or tab) separated list. The fields to be displayed are selected using the <code>-f</code> option. See Section 7.6.2.2.
SQL INSERT statement	<code>-o s</code>	Displays selected fields as an SQL INSERT statement. The fields to be displayed are selected using the <code>-f</code> option. See Section 7.6.2.3.
User specified template	<code>-o t</code>	Displays selected fields in the format specified by the user-specified <i>template</i> . The output template to be used is specified in the <code>-s</code> option. See Section 7.6.2.4.

The default action, if no formatting options are specified, is to display full details of all EXIF and IPTC fields (equivalent to the `'-o a'` option).

7.6.2.1 Full Field Display

The full field display options display all EXIF and/or IPTC fields in an easily read format. It lists each field on its own line, with a full field name and value description. For example:

```
FILE: myphoto.jpg

Camera
  Make           : EASTMAN KODAK COMPANY
  Model          : KODAK DC280 ZOOM DIGITAL CAMERA
  Orientation (start point): Upper Left
  X Resolution   : 192
  Y Resolution   : 192
  Resolution Unit : Inch
  YCbCr Positioning : Centre
  Copyright      : KODAK DC280 ZOOM DIGITAL CAMERA

Image
  Exposure Time (sec) : 1/125
  F-Number           : 8.0
  EXIF Version        : 0210
  Date/Time Taken     : 2000:02:03 06:58:43
  Date/Time Digitised : 2000:02:03 06:58:43
  Components Configuration : 01020300
  Shutter Speed (sec) : 1/128
  Aperture           : 8.0
  Exposure Bias (EV) : 0.00
  Max Aperture       : 2.9
  Metering Mode       : Centre Weighted Average
  Light Source        : Auto
  Flash               : Not Fired
  Focal Length (mm)   : 6.30
  FlashPix Version    : 0100
  Colour Space        : sRGB
```

EXIFutils Command Reference

```
Image Width           : 1760
Image Height          : 1168
Exposure Index        : 100
Sensing Method        : One chip colour area sensor
File Source           : Digital Still Camera
Scene Type            : Directly Photographed Image

Thumbnail
Thumb Compression     : JPEG Compression
Thumb Orientation     : Upper Left
Thumb X Resolution    : 72
Thumb Y Resolution    : 72
Thumb Resolution Unit : Inch
Thumb Jpeg IF Offset  : 1488
Thumb Jpeg IF Byte Count : 6998

InterOp
Interop. Index        : R98
Interop. Version      : 0100

IPTC 2: Editorial
Version               : 2
Date Created          : 2002/11/30
City                  : Sydney
State/Province        : NSW
Country               : Australia
Original Xmit Reference : DCP1234
Mark as Copyrighted   : No

Ricoh Custom Fields
Custom Field 1 Name   : Location
Custom Field 1 Value  : Sydney
Custom Field 2 Name   : Owner
Custom Field 2 Value  : J Smith
Custom Field 3 Name   : Weather
Custom Field 3 Value  : Sunny
Custom Field 4 Name   : Reason
Custom Field 4 Value  : Unknown
Custom Field 5 Name   : Ready
Custom Field 5 Value  : No
```

If the `-o a` option is specified, then all EXIF, IPTC, and RMETA fields present in the file will be displayed. This is the default action if no formatting option is specified.

To display only EXIF fields, use the `-o e` option.

To display only IPTC fields, use the `-o i` option.

To display only RMETA fields, use the `-o r` option.

7.6.2 Field List Display

The field list display formats are intended for use where the output from `exiflist` will be used as input to another program, eg the data is to be imported to a database or spreadsheet. These options display one line for each image file, with the fields separated by either a comma ',' or a tab character. The fields to be displayed are selected using the `-f` option.

The output format to be used is selected using the sub-parameter to the `-o` option:

- `-o l` **Simply Field List:** This is the simplest output format. Field values are displayed as a comma (or tab) separated value list. For example,

```
>exiflist -o l -f file-name,make,f-number myphoto.jpg
myphoto.jpg,KODAK,2.8
>
```

- `-o lh` **Simple Field List with Headings:** This is similar to the `-o l` option, except that the first line lists the field nicknames of the included fields. For example,

```
>exiflist -o lh -f file-name,make,f-number myphoto.jpg
file-name,make,f-number
myphoto.jpg,KODAK,2.8
>
```

- `-o lf` **List with Field Descriptions:** Each field value is preceded by its full field description followed by a colon. For example,

```
>exiflist -o lf -f file-name,make,f-number myphoto.jpg
File Name : myphoto.jpg,Make : KODAK, F-Number : 2.8
>
```

Note that no heading line is displayed.

- `-o ln` **List with Nickname:** Each field value is preceded by its nickname and an equal sign. Each field value is enclosed in quotes ("). For example,

```
>exiflist -o ln -f file-name,make,f-number myphoto.jpg
file-name="myphoto.jpg",make="KODAK",f-number="2.8"
>
```

As with the '`-o lf`' option no heading line is displayed.

This output format is particularly useful as it is the same format that `exifedit -a` accepts as input. This means that `exiflist` and `exifedit` can be used in combination to transfer fields from one image file to another. For example:

```
>exiflist -o ln -f copyright photo.jpg | exifedit -a @- photo2.jpg
```

The above command copies the `copyright` field from `photo.jpg` into `photo2.jpg`.

See the `-k` option for details of changing the quote character that is used.

EXIFutils Command Reference

If any of the fields values contains a new line character, it will be replaced with a semicolon character “;” so that the field output will be on one line. You can use the `-n` option to specify an alternative character to replace newline characters.

If multiple instances of a repeating IPTC field (`ip-keyword` or `ip-suppcat`) are being listed, they will be separated by a semicolon. For example, if a file contains three instances of the IPTC keyword field with the values “trains”, “planes”, and “automobiles”, then listing the `ip-keyword` field will have the following result:

```
>exiflist -o ln -f ip-keyword photo.jpg
ip-keyword="planes; trains; automobiles"
```

You can change the character used to separate repeating IPTC fields by using the `-j` option.

7.6.2.3 SQL Display

The `-o s` option displays the fields of each image file in an SQL INSERT statement. The fields to be displayed are selected by the `-f` option. For example:

```
>exiflist -o s -f file-name,make,f-number myphoto.jpg
INSERT INTO pictures (
  file-name,
  make,
  f-number
) VALUES (
  'myphoto.jpg',
  'EASTMAN KODAK COMPANY',
  8.0
);
>
```

7.6.2.4 User Supplied Template Display

The `-o t` option displays the field values in the format described in the user supplied output template. The output template is specified in the `-s` option, which is mandatory when the `-o t` option is present. A template is a character string containing *markers* that indicate where EXIF and IPTC field values are to be substituted. A marker is any valid EXIFutils nickname surrounded by square brackets: `[]`. For example, see the command and sample output below:

```
>exiflist -o t -s "File: [file-name]\n Make : [make]\n Model: [model]\n\n" \
file1.jpg file2.jpg
File: file1.jpg
  Make : NIKON
  Model: D1X

File: file2.jpg
  Make : KODAK
  Model: DC280

>
```

See Section 6 for a detailed explanation of templates.

7.6.3 Thumbnail Image Extraction

Image files can contain an embedded thumbnail image, which can be extracted into a separate JPG file using the `-t` option. The `-t` option accepts as a parameter either a *file-name-template* that describes the name of the file into which the thumbnail is to be written, or a dot `'.'` indicating that the default file name template is to be used, i.e.

```
-t file-name-template
-t .
```

A *file-name-template* is a string containing markers to indicate where EXIF field values, IPTC field values, and parts of the original file name are to be inserted. See Section 6 for a detailed explanation of templates.

The file name resulting from the *file-name-template* may be a simple file name, or a file name with an absolute or relative directory path. If it is a relative directory path, it will be interpreted as being relative to the directory in which the image file resides, not the current working directory. For example:

```
exiflist -t thumbs/[file-name] mydir/photo.jpg
```

This command will extract the thumbnail image from `mydir/photo.jpg` and store it in a file with the same name as the original image file (`photo.jpg`) in the directory `mydir/thumbs`.

The directory into which the thumbnail file will be written must already exist; `exiflist` will not create it. If the resulting file name exceeds the maximum file name size, the name will be truncated on the right. Any characters that are not valid in file names (`(\V:*?\"<>|)`) will be replaced with a dash `"-`.

If no template is specified (`-t .`) then the following default template used is:

```
[file-base]-th.jpg
```

This will create the thumbnail file in the same directory as the image file, with a name that has the characters `"-th"` inserted before the finale dot in the file name. For example:

```
exiflist -t . mydir/photo.jpg
```

This command will write the thumbnail image to a file called `photo-th.jpg` in the same directory as the image file (`mydir`).

The `-t` option is not supported for all image file types. See Section 7.6.1.1 for a list of image file types that are supported by this option.

7.6.4 Meta Data Extraction

The `exiflist -e` can be used to extract a complete copy of all EXIF, IPTC, and Flashpix data from an image file into a separate `.exi` file. The `.EXI` file can be used to store the EXIF information while the image file is being edited, and later copied back into the image file using the `exifcopy` command. The `-e` option accepts as a parameter either a *file-name-template* that describes the name of the file into which the EXIF data is to be written, or a dot `'.'` indicating that the default template is to be used:

```
-e file-name-template
-e .
```

A *file-name-template* is a string containing markers to indicate where EXIF field values, IPTC field values, and parts of the original file name are to be inserted. See Section 6 for a detailed explanation of templates.

EXIFutils Command Reference

The file name resulting from the *file-name-template* may be a simple file name, or a file name with an absolute or relative directory path. If it is a relative directory path, it will be interpreted as being relative to the directory in which the image file resides, not the current working directory.

For example:

```
exiflist -e exifsave/[file-base].exi mydir/photo.jpg
```

This command will create an EXI save file with the same name as the original image file, but with the file extension changed to `.exi` (i.e. `photo.exi`) in the directory `mydir/exifsave`.

The directory into which the EXI file will be written must already exist; `exiflist` will not create it. If the resulting file name exceeds the maximum file name size, the name will be truncated on the right. Any characters that are not valid in file names (`\V:*?\"<>|`) will be replaced with a dash “-”.

If no template is specified (`-e .`) then the following default template used is:

```
[file-base].exi
```

This will create the EXIF save file in the same directory as the image file, with the file name extension changed to `.exi`. For example:

```
exiflist -e . mydir/photo.jpg
```

This command will write the EXIF information to a file called `photo.exi` in the same directory as the image file (`mydir`).

The `-e` option is not supported for all image file types. See Section 7.6.1.1 for a list of image file types that are supported by this option.

7.6.5 Audio Stream Extraction

Image files can contain an embedded Flashpix audio stream, which can be extracted into a separate WAVE format file using the `-w` option. The `-w` option accepts as a parameter either a *file-name-template* that describes the name of the file into which the audio stream is to be written, or a dot `.` indicating that the default template is to be used:

```
-w file-name-template  
-w .
```

A *file-name-template* is a string containing marks to indicate where EXIF field values, IPTC field values, and parts of the original file name are to be inserted. See Section 6 for a detailed explanation of templates.

The file name resulting from the *file-name-template* may be a simple file name, or a file name preceded by an absolute or relative directory path. If it is a relative directory path, it will be interpreted as being relative to the directory in which the image file resides, not the current working directory. For example:

```
exiflist -w audio/[file-base]-audio.wav mydir/photo.jpg
```

This command will create a `.wav` audio file with the name `photo-audio.wav` in the directory `mydir/audio`

The directory into which the `.wav` file will be written must already exist; `exiflist` will not create it. If the resulting file name exceeds the maximum file name size, the name will be truncated on the right. Any characters that are not valid in file names (`\V:*?\"<>|`) will be replaced with a dash “-”.

See Section 6 for a detailed explanation of templates.

EXIFutils Command Reference

If no template is specified (`-w .`) then the default template used is:

```
[file-base].wav
```

This will create the WAVE audio file in the same directory as the image file, with a name that has the “.jpg” file extension replaced with “.wav”. For example:

```
exiflist -w . mydir/photo.jpg
```

This command will write the audio stream to a file called `photo.wav` in the same directory as the image file (`mydir`).

The `-w` option is not supported for all image file types. See Section 7.6.1.1 for a list of image file types that are supported by this option.

7.6.6 Field Attribute List Options

`exiflist` is used to list details of the EXIF and IPTC fields that can be displayed, edited and copied by the EXIFutils. `exiflist` provides three ways of displaying EXIF field information:

1. List nicknames of all fields (`-l n` option). See Section 8 for an example of the output from this command option.
2. List names of all fields and the values to which they can be set (`-l f` option). See the EXIFutils Field Reference Guide for an example of the output from this command option.
3. List details of one or more specific fields (`-l fieldlist` option). The produces output in the same format as the `-l f` option, but lists details of only those fields specified in the `-l` option. See Section 8.1 for an explanation of the output format. eg:

```
exiflist -l description,make,model
```

7.6.7 Character Set List Options

The character sets used by EXIFutils commands to interpret EXIF and IPTC text fields can be set using the `-p` option, and using environment variables. To determine what character sets EXIFutils is used, the `exiflist -i` option is used. The following command will display the character sets that EXIFutils commands will use:

```
exiflist -i
```

This command displays the current character set setting in the following format:

```
Command Character Set: ISO-8859-1,  
EXIF Character Set    : LATIN1  
IPTC Character Set    : LATIN1
```

The `-i` can be used in combination with the `-p` option to verify that the required character sets are being used, for example:

```
exiflist -p exif=utf8 -i
```

```
Command Character Set: ISO-8859-1,  
EXIF Character Set    : UTF8  
IPTC Character Set    : LATIN1
```

EXIFutils Command Reference

7.6.8 Command Syntax

```
exiflist [-a] [-q] [-u] [-r] [-x] [-j x] [-n x] -o [a|e|i] \
        [-p cmd=charset,exif=charset,iptc=charset] file...

exiflist [-a] [-q] [-u] [-r] [-x] [-j x] [-k x] [-n x] -o [l|lh|ln|lf] \
        [-c [c|t]] [-f field-list] \
        [-p cmd=charset,exif=charset,iptc=charset] file...

exiflist [-a] [-q] [-u] [-r] [-x] [-j x] [-k x] [-n x] -o s [-f field-list] \
        [-p cmd=charset,exif=charset,iptc=charset] file...

exiflist [-a] [-q] [-u] [-r] [-x] [-j x] [-k x] [-n x] -o t -s output-template \
        [-p cmd=charset,exif=charset,iptc=charset] file...

exiflist [-a] [-q] -t [.|file-name-template] \
        [-p cmd=charset,exif=charset,iptc=charset] file...

exiflist [-a] [-q] -w [.|file-name-template] \
        [-p cmd=charset,exif=charset,iptc=charset] file...

exiflist [-a] [-q] -e [.|file-name-template] \
        [-p cmd=charset,exif=charset,iptc=charset] file...

exiflist -i [-p cmd=charset,exif=charset,iptc=charset]

exiflist -l [f|n|field-list]
exiflist [-h|-v]
```

- a Show absolute directory paths. When the directory name is displayed, the full directory path will be shown. By default only the path relative the current directory is shown.
- c [c|t] Specify the field separator character to be used by the -l option; c = comma, t = tab. By default commas are used.
- e [.|file-name-template] Extract a copy of all EXIF, IPTC, and Flashpix Meta data from the specified image file(s) and write it to a separate file. The directory into which the file is written, and the name of the file, is specified in the *file-name-template*. For example:

```
-e "[file-base]-save.[file-ext]"
```

To use the default thumbnail template, specify:

```
-e .
```

The default *file-name-template* is:

```
[file-base].exi
```

See Section 7.6.4 “Meta Data Extraction”, and Section 6 “Templates” or more information about the use of templates.

EXIFutils Command Reference

`-f [field-name,field-name,... | @file-name | @-]`

Specifies the names of the fields that are to be displayed by the field list (`-o l`, `-o lh`, `-o ln`, `-o lf`) and SQL (`-o s`) options. This parameter can be specified in one of three ways:

- 1) a comma separated list of field names on the command line, for example:

```
-f file-name,width,height,ip-caption
```

- 2) an “@” followed by the name of a text file containing a list of the field names to be displayed, separated by commas.

```
-f @field-list.txt
```

- 3) an “@” followed by a '-', indicating that the list of the field names is to be read from stdin, for example:

```
-f @-
```

Use the `-l` option to list the valid field names that can be specified in the field list.

If the `-f` option is not specified, the following default set of fields will be displayed:

```
file-name-full
width
height
exp-time
f-number
date-taken
exp-prog
shutter
aperture
exp-bias
meter-mode
flash
```

See also Section 3.1 “Selecting Multiple Fields”.

`-h` Display `exiflist` usage information

`-i` Display character sets to be used (see `-p` option).

`-j [x|0xnn|0nnn]`

Specify the field separator character to be used to separate repeating IPTC fields. This can be specified in one of three ways:

- o As a printable character, for example `-j +`
- o As a hexadecimal value, for example `-j 0x10`
- o As an octal value with a leading zero, for example `-j 020`

The default value is a semicolon ‘;’

`-k x` Set the quote character used by the `-o` options to the character ‘x’. For example, to set the quote character to be a colon use:

```
-k :
```

EXIFutils Command Reference

`-l [f|n|field-list]`

Displays information about EXIF and IPTC fields. The fields to be displayed, and the level of detail to be displayed about each field, are selected by the sub-parameter. The sub-parameters are:

- `-l f` Display a list of all fields, with details of the valid values to which each field can be set
- `-l n` Display a list of the nicknames of all fields
- `-l field-list` For the fields specified in *field-list*, display details of the valid values to which each field can be set

The `-l` option cannot be use with any other option.

`-n [x|0xnn|Onnn)`

Specify the character to be used to replace any new line characters that appear in field values. This can be specified in one of three ways:

- o As a printable character, for example `-n +`
- o As a hexadecimal value, for example `-n 0x10`
- o As an octal value with a leading zero, for example `-n 020`

The default value is a semicolon `;`

`-o [a|e|i|l|lh|lf|ln|s|t]`

Specifies the output format to be used. Available options are:

Full Field Display Options:

- `-o a` Display all EXIF, IPTC, and RMETA fields. This is the default if no formatting options are present
- `-o e` Display only EXIF fields
- `-o i` Display only IPTC fields
- `-o r` Display only RMETA fields

Field List Options:

- `-o l` Display field values in a comma (or tab) separated list
- `-o lh` As for `-o l` but a heading line is displayed containing field nicknames
- `-o lf` Display field values preceded by their full field description
- `-o ln` Display field values preceded by their field nickname. All field values are surrounded by quotes (`"`).

SQL Output Option:

- `-o s` Display fields as an SQL INSERT statement. One INSERT statement is displayed for each file.

User-Specified Template Option:

- `-o t` Display fields in the format supplied by the *output-template* in the `-s` option.

The fields to be displayed by the field list and SQL output options are selected using the `-f` option. The field separator character to be used (comma or tab) is selected using the `-c` option. The separator character to be used to separate repeating IPTC fields is selected by the `-j` option. The quote character to be used is selected by the `-k` option.

`-p [cmd=xxx],[exif=xxx],[iptc=xxx]`

Specify the character sets to be used when interpreting/displaying text fields

- `cmd=xxx` sets the charset to be used for output displayed from this command.
- `exif=xxx` sets the charset to be used for reading/writing EXIF text fields
- `iptc=xxx` sets the charset to be used for reading/writing IPTC text fields

Any of the three may be omitted. For example:

EXIFutils Command Reference

```
-p exif=latin1,iptc=mac
-p cmd=utf8
```

These values can also be set using the `EXIFUTILS_CS_CMD`, `EXIFUTILS_CS_EXIF`, `EXIFUTILS_CS_IPTC` environment variables.

See Section 5 “Character Sets” for more information.

`-q` Quiet mode. Do not display warning messages

`-r` Recursive mode. If any of the files specified is a directory, then image files in the specified directory and all of its subdirectories will be processed.

`-s [template|@file-name|@-]`
Specifies the *output-template* to be used by the `-o t` option. This option can be specified in one of three ways:

1) on the command line, for example:

```
-s "[file-name]\t[date-taken]\t[model]"
```

2) as an “@” followed by the name of a text file containing the *output-template*:

```
-s @template.txt
```

3) as an “@” followed by a ‘-’, indicating that the *output-template* is to be read from stdin, for example:

```
-s @-
```

`-t [.|file-name-template]`
Extract a copy of the thumbnail image from the specified image file(s) and write them to a separate file. The directory into which the file is written, and the name of the file, is specified in the *file-name-template*. For example:

```
-t "[file-base]-thumb.[file-ext]"
```

To use the default thumbnail template, specify:

```
-t .
```

The default *file-name-template* is:

```
[file-base]-th.jpg
```

See Section 7.6.3 “Thumbnail Image Extraction”, and Section 6 for more information about the use of templates.

`-u` Unformatted mode. `exiflist` will not interpret field values, it will display them as raw values. For example, the shutter speed value 1/125 sec will be displayed uninterpreted as 70/10 in unformatted mode.

`-v` Display program version and licensing information. This is the default action if no other options are present.

`-w [.|file-name-template]`

EXIFutils Command Reference

Extract a copy of the Flashpix audio stream from the specified image file(s) and write it to a separate file. The directory into which the file is written, and the name of the file, is specified in the *file-name-template*. For example:

```
-w "[file-base]-audio.WAV"
```

To use the default audio file name template, specify:

```
-w .
```

The default *file-name-template* is:

```
[file-base].wav
```

See Section 7.6.5 “Audio Stream Extraction” and Section 6 “Templates” for more information about the use of templates.

-x Microsoft Excel compatibility mode. When importing *exiflist* output into Microsoft Excel, Excel does not correctly interpret some EXIF field values (eg: Microsoft Excel™ does not recognise the EXIF date/time format). In Microsoft Excel compatibility mode *exiflist* adjusts the format of certain fields so that Microsoft Excel interprets them correctly. This option is ignored if unformatted mode (*-u*) is also specified.

7.6.9 Examples

```
exiflist image1.jpg image2.tif
```

Displays all EXIF, IPTC, and RMETA information from the image files *image1.jpg* and *image2.tif*

```
exiflist -q -r -o 1 .
```

Displays a summary of EXIF information from all image files in the current directory and all of its subdirectories (*-r* option). Information will be displayed one line per image file (*-o 1* option), and warning messages will be suppressed (*-q* option).

```
exiflist -o 1 -c t ../pics /usr/users/fred image1.jpg
```

Displays EXIF and IPTC information from all image files in the two specified directories (*../pics* and */usr/users/fred*), and for the file *image1.jpg* in the current directory. Information will be displayed one line per file (*-o 1* option) with a tab character separating each field (*-c t* option). As the *-f* option is not present, a selection of commonly used EXIF fields will be displayed (see Section 3.1 for more information on the commonly used fields that will be displayed).

```
exiflist -o lh -f file-name,width,height .
```

Displays the file name, image width, and image height, one line per image file, for all image files in the current directory. One line will be printed for each file. A heading line listing the field names will be displayed as the first line (*-o lh* option).

```
exiflist -o lh -f @file-list.txt .
```

EXIFutils Command Reference

For all image files in the current directory, displays the fields specified in the file `file-list.txt`. A heading line listing the field names will be displayed as the first line (`-o lh` option). The contents of `file-list.txt` must be a comma-separated list of field nicknames, for example:

```
description, comment,  
date-taken, f-number, shutter
```

New line characters in the file are ignored by `exiflist`.

```
exiflist -o l -f aperture image.jpg
```

Displays the camera aperture setting used when `image.jpg` was taken.

```
exiflist -l n
```

List all of the valid field nicknames that can be specified in field lists. Section 8 contains a complete listing of the output from this command.

```
exiflist -l f
```

List all EXIF and IPTC fields and the valid values to which they can be set. The EXIFutils Field Reference Guide contains a complete listing of the output from this command, and an explanation of the output format.

```
exiflist -l gps\*,width,height
```

List the descriptions and valid values for all fields whose nickname begins with “gps”, and for the `width` and `height` fields.

```
exiflist -o t -s @template.txt mydir
```

Displays fields from all image files in `mydir`, using the output format specified in the output-template read from `template.txt`. A sample `template.txt` is included below:

```
File-name: [file-name]  
  Taken on: [date-taken]  
  Shutter Speed: [shutter]  
  F-Stop: [f-number]  
  Compensation: [exp-bias]
```

With this template, the output would be as follows:

```
File-name: myphoto1.jpg  
  Taken on: 2003:01:01 07:00:00  
  Shutter Speed: 1/125  
  F-Stop: 2.8  
  Compensation: 0.00  
  
File-name: photo2.jpg  
  Taken on: 2003:01:01 08:14:34  
  Shutter Speed: 1/60  
  F-Stop: 5.6  
  Compensation: -0.5
```

EXIFutils Command Reference

```
exiflist -t "[file-base]-thumb.jpg" image1.jpg
```

Extracts the EXIF thumbnail file from the image file `image1.jpg` and writes it to a file called `image1-thumb.jpg`.

```
exiflist -e . image1.jpg
```

Takes a copy of the Meta data from the file `image1.jpg` and writes it to a file called `image1.exi`.

```
exiflist -o i -p iptc=mac image1.jpg
```

Display all IPTC fields that are present in `image1.jpg`. All IPTC text fields in the image will be interpreted using the Mac Roman character set.

8 EXIFutils Field Nicknames

8.1 Explanation of Field List Format

The field information in the sections below was generated using the command `'exiflist -l n'`. Table 17 explains the information provided for each field.

Table 17 Explanation of Field List Information

Heading	Explanation	
Field Name	The EXIFutils nickname for this field, which can be used to reference this field in EXIFutils commands.	
Attr	Field Attributes. This contains four characters that provide information about the field.	
	1 st character	Indicates whether this field is included in the <code>exif-common</code> or <code>iptc</code> group nicknames (Refer to EXIFutils Getting Started Guide). Possible values are: 'E' – this field is included in the <code>exif-common</code> group nickname 'I' – this field is included in the <code>iptc</code> group nickname '-' – this field is not included in either <code>exif-common</code> or <code>iptc</code>
	2 nd character	Indicates whether EXIFutils supports reading of this field value. Possible values are: 'R' – this field is readable '-' – this field is not readable
	3 rd character	Indicates whether EXIFutils supports writing of this field. "Writing" means that this field can be individually edited by <code>exifedit</code> . Possible values are: 'W' – editing of this field is supported '-' – editing of this field is not supported
	4 th character	Indicates whether this field is a "standard" field. Possible values are: 'S' – this field is defined in the relevant standard (see note 1). '-' – this is not a standard field. Either it is a proprietary field defined by a camera maker, or is a field defined by EXIFutils.
Tag	<p>For EXIF and TIFF fields, this is the numeric tag that identifies the field. It is supplied for reference purposes only.</p> <p>For IPTC fields, this value shows the dataset number and field number that together uniquely identify the IPTC field. They are show in the format <code>x.y</code> where 'x' is the dataset number and y is the field number.</p> <p>The dataset number is used to group related IPTC fields together. Many Meta data editing applications only support fields in Dataset 2, the "Editorial" fields. These applications typically do not show the dataset number when referring to the field as it is assumed to be the "Editorial" dataset.</p>	
Description	A brief description of the contents of the field.	

Note 1:

- Standard EXIF fields are defined in "JEITA CP-3451, Exchangeable image file format for digital still cameras: Exif Version 2.2".
- Standard TIFF fields are defined in "TIFF, Revision 6.0, Final — June 3, 1992".
- Standard IPTC fields are defined in "IPTC - NAA Information Interchange Model, Version No. 4, Rev 1, July 1999"

EXIFutils Command Reference

8.2 File Attribute Fields

Refer to Section 8.1 for an explanation of the field information shown here.

Field Name	Attr	Tag	Description
file-name	-R--	N/A	File name
file-base	-R--	N/A	Base file name
file-ext	-R--	N/A	File name extension
file-name-full	-R--	N/A	File name with path
file-dir	-R--	N/A	File directory
file-size	-R--	N/A	File size in bytes
file-date-mod	-R--	N/A	File date modified
file-date-created	-R--	N/A	File date created (Windows only)
file-name-thumb	-R--	N/A	Thumbnail file name
file-name-audio	-R--	N/A	Audio file name
file-name-backup	-R--	N/A	Backup file name
file-name-exi	-R--	N/A	EXIF Save file name

8.3 EXIF Date Taken Component Fields

Field Name	Attr	Tag	Description
YYYY	-R--	N/A	Date Taken - Year (4 digits)
YY	-R--	N/A	Date Taken - Year (2 digits)
mm	-R--	N/A	Date Taken - Month (2 digits)
mmm	-R--	N/A	Date Taken - Month (3 letters)
dd	-R--	N/A	Date Taken - Day (2 digits)
hr	-R--	N/A	Date Taken - Hour (2 digits 24hr)
min	-R--	N/A	Date Taken - Minute (2 digits)
sec	-R--	N/A	Date Taken - Seconds (2 digits)

8.4 Standard EXIF Fields

Refer to Section 8.1 for an explanation of the field information shown here.

Field Name	Attr	Tag	Description
InterOp			
iop-index	ERWS	0001	Interop. Index
iop-ver	ERWS	0002	Interop. Version
iop-form	ERWS	1000	Related File Format
iop-width	ERWS	1001	Related Image Width
iop-length	ERWS	1002	Related Image Length
Camera			
acd-comment	-RW-	000b	ACD Comment
image-type	-RWS	00fe	Image Type
main-width	-RWS	0100	Main Image Width
main-len	-RWS	0101	Main Image Length
main-bits-sam	-RWS	0102	Main Image Bits/Sample
main-comp	-RWS	0103	Main Image Compression
photo-int	ERWS	0106	PhotometricInterpret.
doc-name	ERWS	010d	Document Name
description	ERWS	010e	Description
make	ERWS	010f	Make
model	ERWS	0110	Model
strip-off	-R-S	0111	Strip Offsets
orient	ERWS	0112	Orientation (start point)
sample-pix	ERWS	0115	Sample per Pixel
row-strip	-R-S	0116	Rows per Strip

EXIFutils Command Reference

strip-cnt	-R-S	0117	Strip Byte Count
x-res	ERWS	011a	X Resolution
y-res	ERWS	011b	Y Resolution
planar-conf	ERWS	011c	Planar Configuration
page-name	ERWS	011d	Page Name
page-x-pos	ERWS	011e	Page X Position
page-y-pos	ERWS	011f	Page Y Position
res-unit	ERWS	0128	Resolution Unit
page-num	ERWS	0129	Page Number (X of Y)
trans-func	-RWS	012d	Transfer Function
firm-ver	ERWS	0131	Firmware Version
date-mod	ERWS	0132	Date/Time Modified
artist	-RWS	013b	Artist
white-point	ERWS	013e	White Point
prim-chrom	ERWS	013f	Primary Chromatic
sub-ifd	ERWS	014a	Sub-IFD
ycbcr-coeff	ERWS	0211	YCbCr Coefficients
ycbcr-posn	ERWS	0213	YCbCr Positioning
ref-bw	ERWS	0214	Reference Black&White
xp-title-text	ERWS	0320	XP Title Text
camera-num	ERWS	827d	Camera Number
copyright	ERWS	8298	Copyright
comment-old	-RW-	9286	User Comment (EXIF 2.0)
xp-rating	-RW-	4746	XP Rating (1-5,0=Unrated)
xp-dip-tags	-RW-	4747	Digital Image Pro Tags
xp-title	-RW-	9c9b	XP Title
xp-comment	-RW-	9c9c	XP Comment
xp-author	-RW-	9c9d	XP Author
xp-keyword	-RW-	9c9e	XP Keywords
xp-subject	-RW-	9c9f	XP Subject
print-im	-RWS	c4a5	Print Image Matching
Image			
exp-time	ERWS	829a	Exposure Time (sec)
f-number	ERWS	829d	F-Number
exp-prog	ERWS	8822	Exposure Program
spec-sens	ERWS	8824	Spectral Sensitivity
iso-speed	ERWS	8827	ISO Speed
oecf	ERWS	8828	Optoelectric Conv. Factor
exif-ver	ERWS	9000	EXIF Version
date-taken	ERWS	9003	Date/Time Taken
date-digi	ERWS	9004	Date/Time Digitised
comp-conf	-RWS	9101	Components Configuration
ave-comp	ERWS	9102	Average Compression Ratio
shutter	ERWS	9201	Shutter Speed (sec)
aperture	ERWS	9202	Aperture
brightness	ERWS	9203	Brightness
exp-bias	ERWS	9204	Exposure Bias (EV)
max-aper	ERWS	9205	Max Aperture
subj-dist	ERWS	9206	Subject Distance (metres)
meter-mode	ERWS	9207	Metering Mode
light-src	ERWS	9208	Light Source
flash	ERWS	9209	Flash
focal-len	ERWS	920a	Focal Length (mm)
history	ERWS	9213	Image History
subj-area	ERWS	9214	Subject Area
maker-note	-R-S	927c	Maker Note

EXIFutils Command Reference

comment	ERWS	9286	User Comment
sub-time	ERWS	9290	Subsec Time
sub-time-orig	ERWS	9291	Subsec Time Original
sub-time-digi	ERWS	9292	Subsec Time Digitised
flashpix-ver	-RWS	a000	FlashPix Version
colour-space	ERWS	a001	Colour Space
width	ERWS	a002	Image Width
height	ERWS	a003	Image Height
sound-file	ERWS	a004	Related Sound File
inter-offset	-R-S	a005	EXIF Inter. Offset
sfr	-RWS	a20c	Spatial Freq. Response
flash-energy	ERWS	a20b	Flash Energy (BCPS)
fp-x-res	ERWS	a20e	Focal Plane X Resolution
fp-y-res	ERWS	a20f	Focal Plane Y Resolution
fp-res-unit	ERWS	a210	Focal Plane Res. Unit
subj-locn	ERWS	a214	Subject Location
exp-index	ERWS	a215	Exposure Index
sense-method	ERWS	a217	Sensing Method
file-src	ERWS	a300	File Source
scene-type	ERWS	a301	Scene Type
cfa-pattern	-RWS	a302	CFA Pattern
custom-render	ERWS	a401	Custom Render
exp-mode	ERWS	a402	Exposure Mode
white-bal	ERWS	a403	White Balance
digital-zoom	ERWS	a404	Digital Zoom Ratio
focal-len-35mm	ERWS	a405	Focal Length (35mm equiv)
scene-mode	ERWS	a406	Scene Capture Mode
gain	ERWS	a407	Gain Control
contrast	ERWS	a408	Contrast
saturation	ERWS	a409	Saturation
sharpness	ERWS	a40a	Sharpness
dev-setting	-RWS	a40b	Device Setting
subj-range	ERWS	a40c	Subject Distance Range
image-id	ERWS	a420	Unique Image Id
Thumbnail			
th-width	ERWS	0100	Thumb Image Width
th-len	ERWS	0101	Thumb Image Length
th-bits-sam	-RWS	0102	Thumb Bits per Sample
th-comp	ERWS	0103	Thumb Compression
th-photo-int	ERWS	0106	Thumb PhotometricInterp.
th-description	ERWS	010e	Thumb Description
th-make	ERWS	010f	Thumb Make
th-model	ERWS	0110	Thumb Model
th-strip-off	-R-S	0111	Thumb Strip Offsets
th-orient	ERWS	0112	Thumb Orientation
th-sample-pix	ERWS	0115	Thumb Sample per Pixel
th-row-strip	ER-S	0116	Thumb Rows per Strip
th-strip-cnt	ER-S	0117	Thumb Strip Byte Count(s)
th-x-res	ERWS	011a	Thumb X Resolution
th-y-res	ERWS	011b	Thumb Y Resolution
th-plan-conf	ERWS	011c	Thumb Planar Config
th-res-unit	ERWS	0128	Thumb Resolution Unit
th-firm-ver	ERWS	0131	Thumb Firmware Version
th-date-mod	ERWS	0132	Thumb Date/Time Modified
th-artist	-RWS	013b	Thumb Artist
th-white-point	ERWS	013e	Thumb White Point

EXIFutils Command Reference

th-prim-chrom	ERWS	013f	Thumb Primary Chromatic
th-if-offset	ERWS	0201	Thumb Jpeg IF Offset
th-if-count	ERWS	0202	Thumb Jpeg IF Byte Count
th-ybcr-coeff	ERWS	0211	Thumb YCbCr Coefficients
th-ybcr-sub	ERWS	0212	Thumb YCbCr Sub-Sampling
th-ybcr-posn	ERWS	0213	Thumb YCbCr Positioning
th-ref-bw	ERWS	0214	Thumb Reference Black/White
th-copyright	ERWS	8298	Thumb Copyright

GPS

gps-ver	-RWS	0000	Version
gps-lat-ref	-RWS	0001	Latitude Reference
gps-latitude	-RWS	0002	Latitude
gps-long-ref	-RWS	0003	Longitude Reference
gps-longitude	-RWS	0004	Longitude
gps-alt-ref	-RWS	0005	Altitude Reference
gps-altitude	-RWS	0006	Altitude
gps-time	-RWS	0007	Time
gps-satellite	-RWS	0008	Satellite
gps-recv-stat	-RWS	0009	Receive Status
gps-mode	-RWS	000a	Measurement Mode
gps-precision	-RWS	000b	Measurement Precision
gps-speed-unit	-RWS	000c	Speed Unit
gps-recv-speed	-RWS	000d	Receiver Speed
gps-mov-dir-ref	-RWS	000e	Movement Direction Ref
gps-mov-dir	-RWS	000f	Movement Direction
gps-img-dir-ref	-RWS	0010	Image Direction Ref
gps-img-dir	-RWS	0011	Image Direction
gps-geodetic	-RWS	0012	Geodetic Survey Data
gps-dest-lat-ref	-RWS	0013	Dest. Latitude Ref
gps-dest-lat	-RWS	0014	Destination Latitude
gps-dest-long-ref	-RWS	0015	Dest. Longitude Ref
gps-dest-long	-RWS	0016	Destination Longitude
gps-dest-bear-ref	-RWS	0017	Dest. Bearing Ref
gps-dest-bear	-RWS	0018	Destination Bearing
gps-dest-dist-ref	-RWS	0019	Dest. Distance Ref
gps-dest-dist	-RWS	001a	Destination Distance
gps-proc-method	-RWS	001b	Processing Method
gps-area	-RWS	001c	Area Information
gps-date	-RWS	001d	Datestamp
gps-diff-corr	-RWS	001e	Differential Correction

8.5 TIFF Fields

Refer to Section 8.1 for an explanation of the field information shown here.

----- Field Name -----	-Attr-	-Tag-	----- Description -----
tf-image-type	-RWS	00fe	TIFF Image Type
tf-width	ERWS	0100	TIFF Image Width
tf-len	ERWS	0101	TIFF Image Length
tf-bits-sam	-RWS	0102	TIFF Image Bits/Sample
tf-comp	ERWS	0103	TIFF Image Compression
tf-photo-int	ERWS	0106	TIFF PhotometricInterp.
tf-description	ERWS	010e	TIFF Description
tf-make	ERWS	010f	TIFF Make
tf-model	ERWS	0110	TIFF Model

EXIFutils Command Reference

tf-strip-off	-R-S	0111	TIFF Strip Offsets
tf-orient	ERWS	0112	TIFF Orientation
tf-sample-pix	ER-S	0115	TIFF Sample per Pixel
tf-row-strip	ER-S	0116	TIFF Rows per Strip
tf-strip-cnt	ER-S	0117	TIFF Strip Byte Count(s)
tf-x-res	ERWS	011a	TIFF X Resolution
tf-y-res	ERWS	011b	TIFF Y Resolution
tf-plan-conf	ERWS	011c	TIFF Planar Config
tf-res-unit	ERWS	0128	TIFF Resolution Unit
tf-firm-ver	ERWS	0131	TIFF Firmware Version
tf-date-mod	ERWS	0132	TIFF Date/Time Modified
tf-artist	-RWS	013b	TIFF Artist
tf-white-point	ERWS	013e	TIFF White Point
tf-prim-chrom	ERWS	013f	TIFF Primary Chromatic
tf-if-offset	ERWS	0201	TIFF Jpeg IF Offset
tf-if-count	ERWS	0202	TIFF Jpeg IF Byte Count
tf-ybcr-coeff	ERWS	0211	TIFF YCbCr Coefficients
tf-ybcr-sub	ERWS	0212	TIFF YCbCr Sub-Sampling
tf-ybcr-posn	ERWS	0213	TIFF YCbCr Positioning
tf-ref-bw	ERWS	0214	TIFF Reference Black/White
tf-copyright	ERWS	8298	TIFF Copyright

8.6 Proprietary Make Note Fields

Refer to Section 8.1 for an explanation of the field information shown here.

----- Field Name -----	-Attr-	-Tag-	----- Description -----
Maker Note (Canon PowerShot)			
cn-0000	-RW-	0000	Field 0x0000
cn-macro-mode	-R--	0001	Macro Mode
cn-self-timer	-R--	0001	Self Timer
cn-quality	-R--	0001	Quality
cn-flash-mode	-R--	0001	Flash Mode
cn-drive-mode	-R--	0001	Drive Mode
cn-focus-mode	-R--	0001	Focus Mode
cn-image-size	-R--	0001	Image Size
cn-easy-shoot	-R--	0001	Easy Shoot
cn-digi-zoom	-R--	0001	Digital Zoom
cn-contrast	-R--	0001	Contrast
cn-saturation	-R--	0001	Saturation
cn-sharpness	-R--	0001	Sharpness
cn-iso	-R--	0001	ISO
cn-meter-mode	-R--	0001	Meter Mode
cn-focus-type	-R--	0001	Focus Type
cn-af-point	-R--	0001	AF Point
cn-exp-mode	-R--	0001	Exposure Moded
cn-focal-len-long	-R--	0001	Focal Length Long
cn-focal-len-short	-R--	0001	Focal Length Short
cn-focal-units	-R--	0001	Focal Units per mm
cn-flash-activity	-R--	0001	Flash Activity
cn-flash	-R--	0001	Flash
cn-focus	-R--	0001	Focus
cn-0002	-RW-	0002	Field 0x0002
cn-0003	-RW-	0003	Field 0x0003
cn-white-bal	-R--	0004	White Balance
cn-burst-seq	-R--	0004	Continuous Burst Seq
cn-af-point2	-R--	0004	AF Point (2)

EXIFutils Command Reference

cn-flash-bias	-R--	0004	Flash Bias (EV)
cn-subj-dist	-R--	0004	Subject Distance
cn-0005	-RW-	0005	Field 0x0005
cn-image-type	-RW-	0006	Image Type
cn-firm-ver	-RW-	0007	Firmware Version
cn-image-num	-RW-	0008	Image Number
cn-owner	-RW-	0009	Owner Name
cn-000a	-RW-	000a	Field 0x000a
cn-body-num	-RW-	000c	Camera Body Number
cn-000d	-RW-	000d	Field 0x000d
cn-000e	-RW-	000e	Field 0x000e
cn-noise-reduct	-RW-	000f	Long Exp. Noise Reduct
cn-ae-lock	-RW-	000f	AE Lock Button
cn-mirror-lockup	-RW-	000f	Mirror Lockup
cn-tv-av-exp	-RW-	000f	Tv/Av and Exposure Level
cn-av-assist	-RW-	000f	Av Assist Light
cn-shutter-in-av	-RW-	000f	Shutter in Av Mode
cn-aeb-seq	-RW-	000f	AEB Seq/Auto Cancellation
cn-shutter-curtain	-RW-	000f	Shutter Curtain Sync
cn-lens-func	-RW-	000f	Lens AF Stop Button Func.
cn-fill-flash	-RW-	000f	Auto Reduction Fill Flash
cn-menu-return	-RW-	000f	MENU Button Return Posn
cn-set-button	-RW-	000f	SET Button Function
cn-sensor-cleaning	-RW-	000f	Sensor Cleaning
cn-0010	-RW-	0010	Field 0x0010
cn-0012	-RW-	0012	Field 0x0012
cn-0013	-RW-	0013	Field 0x0013
cn-0015	-RW-	0015	Field 0x0015
cn-0081	-RW-	0081	Field 0x0081
cn-0082	-RW-	0082	Field 0x0082
cn-0083	-RW-	0083	Field 0x0083
cn-0090	-RW-	0090	Field 0x0090
cn-0091	-RW-	0091	Field 0x0091
cn-0092	-RW-	0092	Field 0x0092
cn-0094	-RW-	0094	Field 0x0094
Maker Note (Casio)			
cs-rec-mode	-RW-	0001	Recording Mode
cs-quality	-RW-	0002	Quality
cs-focus-mode	-RW-	0003	Focusing Mode
cs-flash-mode	-RW-	0004	Flash Mode
cs-flash-int	-RW-	0005	Flash Intensity
cs-obj-dist	-RW-	0006	Object Distance
cs-white-bal	-RW-	0007	White Balance
cs-0008	-RW-	0008	Field 0x0008
cs-0009	-RW-	0009	Field 0x0009
cs-digi-zoom	-RW-	000a	Digital Zoom
cs-sharpness	-RW-	000b	Sharpness
cs-contrast	-RW-	000c	Contrast
cs-saturation	-RW-	000d	Saturation
cs-000e	-RW-	000e	Field 0x000e
cs-000f	-RW-	000f	Field 0x000f
cs-0010	-RW-	0010	Field 0x0010
cs-0011	-RW-	0011	Field 0x0011
cs-0012	-RW-	0012	Field 0x0012
cs-0013	-RW-	0013	Field 0x0013
cs-ccd	-RW-	0014	CCD Sensitivity

EXIFutils Command Reference

cs-0015	-RW-	0015	Field 0x0015
cs-0016	-RW-	0016	Field 0x0016
cs-0017	-RW-	0017	Field 0x0017
cs-0018	-RW-	0018	Field 0x0018
cs-0019	-RW-	0019	Field 0x0019
cs-001a	-RW-	001a	Field 0x001a
cs-001c	-RW-	001c	Field 0x001c
cs-001d	-RW-	001d	Field 0x001d
cs-0e00	-RW-	0e00	Field 0x0e00
Maker Note (Epson)			
eps-0209	-RW-	0209	Field 0x0209
eps-0f00	-RW-	0f00	Field 0x0f00
Maker Note (FujiFilm)			
fu-version	-RW-	0000	Version
fu-quality	-RW-	1000	Quality
fu-sharpness	-RW-	1001	Sharpness
fu-white-bal	-RW-	1002	White Balance
fu-1003	-RW-	1003	Field 0x1003
fu-flash-mode	-RW-	1010	Flash Mode
fu-flash-str	-RW-	1011	Flash Strength Comp
fu-macro	-RW-	1020	Macro
fu-focus-mode	-RW-	1021	Focus Mode
fu-1022	-RW-	1022	Field 0x1022
fu-1023	-RW-	1023	Field 0x1023
fu-slow-sync	-RW-	1030	Slow Sync.
fu-picture-mode	-RW-	1031	Picture Mode
fu-bracket	-RW-	1100	Contin/Bracket Mode
fu-1200	-RW-	1200	Field 0x1200
fu-blur-warn	-RW-	1300	Blur Warning
fu-focus-warn	-RW-	1301	Focus Warning
fu-ae-warn	-RW-	1302	AE Warning
Maker Note (Minolta)			
mn-version	-RW-	0000	Version
mns1-exp-mode	-R--	0001	Exposure Mode
mns1-flash-mode	-R--	0001	Flash Mode
mns1-white-bal	-R--	0001	White Balance
mns1-image-dim	-R--	0001	Image Dimensions
mns1-image-qual	-R--	0001	Image Quality
mns1-drive-mode	-R--	0001	Drive Mode
mns1-meter-mode	-R--	0001	Meter Mode
mns1-apex-film-speed	-R--	0001	APEX Film Speed Value
mns1-apex-time	-R--	0001	APEX Time Value
mns1-apex-aperture	-R--	0001	APEX Aperture Value
mns1-macro-mode	-R--	0001	Macro Mode
mns1-digital-zoom	-R--	0001	Digital Zoom
mns1-exp-comp	-R--	0001	Exposure Compensation
mns1-bracket-step	-R--	0001	Bracket Step (EV)
mns1-0003-10	-R--	0001	Field 0x0003-10
mns1-interval-len	-R--	0001	Interval Length (min)
mns1-interval-num	-R--	0001	Num Interval Frames
mns1-focal-len	-R--	0001	Focal Length
mns1-focus-dist	-R--	0001	Focus Distance (meters)
mns1-flashFired	-R--	0001	Flash Fired
mns1-date	-R--	0001	Date

EXIFutils Command Reference

mns1-time	-R--	0001	Time
mns1-max-aper	-R--	0001	Maximum Aperture
mns1-0003-19	-R--	0001	Field 0x0003-19
mns1-0003-1a	-R--	0001	Field 0x0003-1a
mns1-file-num-mem	-R--	0001	File Number Memory
mns1-last-file-num	-R--	0001	Last File Number
mns1-white-bal-red	-R--	0001	White Balance Red
mns1-white-bal-green	-R--	0001	White Balance Green
mns1-white-bal-blue	-R--	0001	White Balance Blue
mns1-saturation	-R--	0001	Saturation
mns1-Contrast	-R--	0001	Contrast
mns1-sharpness	-R--	0001	Sharpness
mns1-subj-prog	-R--	0001	Subject Program
mns1-flash-comp	-R--	0001	Flash Compensation
mns1-iso-setting	-R--	0001	ISO Setting
mns1-model	-R--	0001	Camera Model
mns1-interval-mode	-R--	0001	Interval Mode
mns1-folder-setting	-R--	0001	Folder Name Setting
mns1-color-mode	-R--	0001	Color Mode
mns1-color-filter	-R--	0001	Color Filter
mns1-bw-filter	-R--	0001	Black and White Filter
mns1-internal-flash	-R--	0001	Internal Flash Fired
mns1-apex-bright	-R--	0001	APEX Brightness Value
mns1-spot-focus-x	-R--	0001	Spot Focus X Position
mns1-spot-focus-y	-R--	0001	Spot Focus Y Position
mns1-wide-focus-zone	-R--	0001	AF Wide Focus Zone
mns1-focus-mode	-R--	0001	Focus Mode
mns1-focus-area	-R--	0001	AF Focus Area
mns1-dec-setting	-R--	0001	DEC Setting
mns1-embedded-profile	-R--	0001	Embedded Color Profile
mns1-data-imprint	-R--	0001	Data Imprint
mns1-0003-36	-R--	0001	Field 0x0003-36
mns1-0003-37	-R--	0001	Field 0x0003-37
mns1-0003-38	-R--	0001	Field 0x0003-38
mns1-0003-39	-R--	0001	Field 0x0003-39
mns2-0003-1	-R--	0003	Field 0x0003-1
mns2-exp-mode	-R--	0003	Exposure Mode
mns2-flash-mode	-R--	0003	Flash Mode
mns2-white-bal	-R--	0003	White Balance
mns2-image-dim	-R--	0003	Image Dimensions
mns2-image-qual	-R--	0003	Image Quality
mns2-drive-mode	-R--	0003	Drive Mode
mns2-meter-mode	-R--	0003	Meter Mode
mns2-apex-film-speed	-R--	0003	APEX Film Speed Value
mns2-apex-time	-R--	0003	APEX Time Value
mns2-apex-aperture	-R--	0003	APEX Aperture Value
mns2-macro-mode	-R--	0003	Macro Mode
mns2-digital-zoom	-R--	0003	Digital Zoom
mns2-exp-comp	-R--	0003	Exposure Compensation
mns2-bracket-step	-R--	0003	Bracket Step (EV)
mns2-0003-10	-R--	0003	Field 0x0003-10
mns2-interval-len	-R--	0003	Interval Length (min)
mns2-interval-num	-R--	0003	Num Interval Frames
mns2-focal-len	-R--	0003	Focal Length
mns2-focus-dist	-R--	0003	Focus Distance (meters)
mns2-flashFired	-R--	0003	Flash Fired
mns2-date	-R--	0003	Date

EXIFutils Command Reference

mns2-time	-R--	0003	Time
mns2-max-aper	-R--	0003	Maximum Aperture
mns2-0003-19	-R--	0003	Field 0x0003-19
mns2-0003-1a	-R--	0003	Field 0x0003-1a
mns2-file-num-mem	-R--	0003	File Number Memory
mns2-last-file-num	-R--	0003	Last File Number
mns2-white-bal-red	-R--	0003	White Balance Red
mns2-white-bal-green	-R--	0003	White Balance Green
mns2-white-bal-blue	-R--	0003	White Balance Blue
mns2-saturation	-R--	0003	Saturation
mns2-Contrast	-R--	0003	Contrast
mns2-sharpness	-R--	0003	Sharpness
mns2-subj-prog	-R--	0003	Subject Program
mns2-flash-comp	-R--	0003	Flash Compensation
mns2-iso-setting	-R--	0003	ISO Setting
mns2-model	-R--	0003	Camera Model
mns2-interval-mode	-R--	0003	Interval Mode
mns2-folder-setting	-R--	0003	Folder Name Setting
mns2-color-mode	-R--	0003	Color Mode
mns2-color-filter	-R--	0003	Color Filter
mns2-bw-filter	-R--	0003	Black and White Filter
mns2-internal-flash	-R--	0003	Internal Flash Fired
mns2-apex-bright	-R--	0003	APEX Brightness Value
mns2-spot-focus-x	-R--	0003	Spot Focus X Position
mns2-spot-focus-y	-R--	0003	Spot Focus Y Position
mns2-wide-focus-zone	-R--	0003	AF Wide Focus Zone
mns2-focus-mode	-R--	0003	Focus Mode
mns2-focus-area	-R--	0003	AF Focus Area
mns2-dec-setting	-R--	0003	DEC Setting
mns2-embedded-profile	-R--	0003	Embedded Color Profile
mns2-data-imprint	-R--	0003	Data Imprint
mns2-0003-36	-R--	0003	Field 0x0003-36
mns2-0003-37	-R--	0003	Field 0x0003-37
mns2-0003-38	-R--	0003	Field 0x0003-38
mns2-0003-39	-R--	0003	Field 0x0003-39
mn-0010	-RW-	0010	Field 0x0010
mn-0018	-RW-	0018	Field 0x0018
mn-0020	-RW-	0020	Field 0x0020
mn-image-size	-RW-	0040	Compressed Image Size
mn-thumbnail	-RW-	0081	Thumbnail Image
mn-thumb-offset	-RW-	0088	Thumbnail Offset
mn-thumb-len	-RW-	0089	Thumbnail Length
mn-00e0	-RW-	00e0	Field 0x00e0
mn-0100	-RW-	0100	Field 0x0100
mn-color-mode	-RW-	0101	Color Mode
mn-quality	-RW-	0102	Image Quality
mn-quality2	-RW-	0103	Image Quality 2
mn-0006	-RW-	0106	Field 0x0106
mn-0211	-RW-	0211	Field 0x0211
mn-0212	-RW-	0212	Field 0x0212
mn-0213	-RW-	0213	Field 0x0213
mn-0214	-RW-	0214	Field 0x0214
mn-pim	-RW-	0e00	PIM Information
mn-settings3	-RW-	0f00	Camera Settings 3
Maker Note (Nikon Type 1)			
n1-0002	-RW-	0002	Field 0x0002

EXIFutils Command Reference

n1-quality	-RW-	0003	Quality
n1-col-mode	-RW-	0004	Colour Mode
n1-image-adj	-RW-	0005	Image Adjustment
n1-ccd-sens	-RW-	0006	CCD Sensitivity
n1-white-bal	-RW-	0007	White Balance
n1-focus	-RW-	0008	Focus
n1-0020	-RW-	0009	Field 0x0020
n1-digi-zoom	-RW-	000a	Digital Zoom
n1-converter	-RW-	000b	Lens Converter
n1-0f00	-RW-	0f00	Field 0x0f00

Maker Note (Nikon Type 2)

n2-version	-RW-	0001	Version
n2-iso	-RW-	0002	ISO Setting
n2-color-mode	-RW-	0003	Colour Mode
n2-quality	-RW-	0004	Quality
n2-white-bal	-RW-	0005	White Balance
n2-sharpen	-RW-	0006	Image Sharpening
n2-focus-mode	-RW-	0007	Focus Mode
n2-flash-set	-RW-	0008	Flash Setting
n2-000a	-RW-	000a	Field 0x000a
n2-iso-sel	-RW-	000f	ISO Selection
n2-data-dump	-RW-	0010	Data Dump
n2-image-adj	-RW-	0080	Image Adjustment
n2-adapter	-RW-	0082	Lens Adapter
n2-man-focus	-RW-	0085	Manual Focus Distance
n2-digi-zoom	-RW-	0086	Digital Zoom
n2-focus-posn	-RW-	0088	AF Focus Position
n2-saturation	-RW-	0094	Saturation Adjustment
n2-noise	-RW-	0095	Noise Reduction

Maker Note (Nikon Type 3)

n3-version	-RW-	0001	Version
n3-iso	-RW-	0002	ISO Setting
n3-color-mode	-RW-	0003	Colour Mode
n3-quality	-RW-	0004	Quality
n3-white-bal	-RW-	0005	White Balance
n3-sharp	-RW-	0006	Sharpening
n3-focus	-RW-	0007	Focus
n3-flash-set	-RW-	0008	Flash Setting
n3-flash-mode	-RW-	0009	Flash Mode
n3-000a	-RW-	000a	Field 0x000a
n3-white-bias	-RW-	000b	White Balance Bias
n3-000c	-RW-	000c	Field 0x000c
n3-000d	-RW-	000d	Field 0x000d
n3-exp-diff	-RW-	000e	Exposure Difference
n3-iso-sel	-RW-	000f	ISO Selection
n3-0010	-RW-	0010	Field 0x0010
n3-thumb-offset	-R--	0011	Thumbnail IFD Offset
n3-flash-comp	-RW-	0012	Flash Compensation
n3-0013	-RW-	0013	Field 0x0013
n3-0017	-RW-	0017	Field 0x0017
n3-0018	-RW-	0018	Field 0x0018
n3-0019	-RW-	0019	Field 0x0019
n3-image-adj	-RW-	0080	Image Adjustment
n3-tone-comp	-RW-	0081	Tone Compensation
n3-lens-type	-RW-	0083	Lens Type

EXIFutils Command Reference

n3-lens	-RW-	0084	Lens
n3-man-focus	-RW-	0085	Manual Focus Distance
n3-digi-zoom	-RW-	0086	Digital Zoom
n3-flash-used	-RW-	0087	Flash Used
n3-focus-posn	-RW-	0088	AF Focus Position
n3-bracket	-RW-	0089	Bracketing
n3-008a	-RW-	008a	Field 0x008a
n3-008b	-RW-	008b	Field 0x008b
n3-color-mode2	-RW-	008d	Color Mode
n3-008e	-RW-	008e	Field 0x008e
n3-light-type	-RW-	0090	Lighting Type
n3-0091	-RW-	0091	Field 0x0091
n3-hue-adj	-RW-	0092	Hue Adjustment
n3-saturation	-RW-	0094	Saturation Adjustment
n3-noise	-RW-	0095	Noise Reduction
n3-0091	-RW-	0097	Field 0x0091
n3-0098	-RW-	0098	Field 0x0098
n3-009a	-RW-	009a	Field 0x009a
n3-0103	-RW-	0103	Field 0x0103
n3-0e10	-RW-	0e10	Field 0x0e10

Maker Note (Olympus)

ol-spec-mode	-RW-	0200	Special Mode
ol-jpg-qual	-RW-	0201	JPEG Quality
ol-macro	-RW-	0202	Macro
ol-0203	-RW-	0203	Field 0x0203
ol-digi-zoom	-RW-	0204	Digital Zoom
ol-0205	-RW-	0205	Field 0x0205
ol-0206	-RW-	0206	Field 0x0206
ol-sw-rel	-RW-	0207	Software Release
ol-pic-info	-RW-	0208	Picture Information
ol-camera-id	-RW-	0209	Camera Id
ol-data-dump	-RW-	0f00	Data Dump

Maker Note (Olympus C2500L)

olc25001-spec-mode	-RW-	0200	Special Mode
olc25001-jpg-qual	-RW-	0201	JPEG Quality
olc25001-macro	-RW-	0202	Macro
olc25001-0203	-RW-	0203	Field 0x0203
olc25001-digi-zoom	-RW-	0204	Digital Zoom
olc25001-0205	-RW-	0205	Field 0x0205
olc25001-0206	-RW-	0206	Field 0x0206
olc25001-sw-rel	-RW-	0207	Software Release
olc25001-pic-info	-RW-	0208	Picture Information
olc25001-camera-id	-RW-	0209	Camera Id
olc25001-data-dump	-RW-	0f00	Data Dump
olc25001-1000	-RW-	1000	Field 0x1000
olc25001-1001	-RW-	1001	Field 0x1001
olc25001-1002	-RW-	1002	Field 0x1002
olc25001-1003	-RW-	1003	Field 0x1003
olc25001-1004	-RW-	1004	Field 0x1004
olc25001-1005	-RW-	1005	Field 0x1005
olc25001-1006	-RW-	1006	Field 0x1006
olc25001-1007	-RW-	1007	Field 0x1007
olc25001-1008	-RW-	1008	Field 0x1008
olc25001-1009	-RW-	1009	Field 0x1009
olc25001-100a	-RW-	100a	Field 0x100a

EXIFutils Command Reference

olc25001-100b	-RW-	100b	Field	0x100b
olc25001-100c	-RW-	100c	Field	0x100c
olc25001-100d	-RW-	100d	Field	0x100d
olc25001-100e	-RW-	100e	Field	0x100e
olc25001-100f	-RW-	100f	Field	0x100f
olc25001-1010	-RW-	1010	Field	0x1010
olc25001-1011	-RW-	1011	Field	0x1011
olc25001-1012	-RW-	1012	Field	0x1012
olc25001-1013	-RW-	1013	Field	0x1013
olc25001-1014	-RW-	1014	Field	0x1014
olc25001-1015	-RW-	1015	Field	0x1015
olc25001-1016	-RW-	1016	Field	0x1016
olc25001-1017	-RW-	1017	Field	0x1017
olc25001-1018	-RW-	1018	Field	0x1018
olc25001-1019	-RW-	1019	Field	0x1019
olc25001-101a	-RW-	101a	Field	0x101a
olc25001-101b	-RW-	101b	Field	0x101b
olc25001-101c	-RW-	101c	Field	0x101c
olc25001-101d	-RW-	101d	Field	0x101d
olc25001-101e	-RW-	101e	Field	0x101e
olc25001-101f	-RW-	101f	Field	0x101f
olc25001-1020	-RW-	1020	Field	0x1020
olc25001-1021	-RW-	1021	Field	0x1021
olc25001-1022	-RW-	1022	Field	0x1022
olc25001-1023	-RW-	1023	Field	0x1023
olc25001-1024	-RW-	1024	Field	0x1024
olc25001-1025	-RW-	1025	Field	0x1025
olc25001-1026	-RW-	1026	Field	0x1026
olc25001-1027	-RW-	1027	Field	0x1027
olc25001-1028	-RW-	1028	Field	0x1028

Maker Note (Olympus E-20, E-20N, E-20P)

ole-0200	-RW-	0200	Field	0x0200
ole-0201	-RW-	0201	Field	0x0201
ole-0202	-RW-	0202	Field	0x0202
ole-0203	-RW-	0203	Field	0x0203
ole-0204	-RW-	0204	Field	0x0204
ole-0205	-RW-	0205	Field	0x0205
ole-0206	-RW-	0206	Field	0x0206
ole-0207	-RW-	0207	Field	0x0207
ole-0208	-RW-	0208	Field	0x0208
ole-0209	-RW-	0209	Field	0x0209
ole-0f00	-RW-	0f00	Field	0x0f00
ole-1000	-RW-	1000	Field	0x1000
ole-1001	-RW-	1001	Field	0x1001
ole-1002	-RW-	1002	Field	0x1002
ole-1003	-RW-	1003	Field	0x1003
ole-1004	-RW-	1004	Field	0x1004
ole-1005	-RW-	1005	Field	0x1005
ole-1006	-RW-	1006	Field	0x1006
ole-1007	-RW-	1007	Field	0x1007
ole-1008	-RW-	1008	Field	0x1008
ole-1009	-RW-	1009	Field	0x1009
ole-100a	-RW-	100a	Field	0x100a
ole-100b	-RW-	100b	Field	0x100b
ole-100c	-RW-	100c	Field	0x100c
ole-100d	-RW-	100d	Field	0x100d

EXIFutils Command Reference

ole-100e	-RW-	100e	Field 0x100e
ole-100f	-RW-	100f	Field 0x100f
ole-1010	-RW-	1010	Field 0x1010
ole-1011	-RW-	1011	Field 0x1011
ole-1012	-RW-	1012	Field 0x1012
ole-1013	-RW-	1013	Field 0x1013
ole-1014	-RW-	1014	Field 0x1014
ole-1015	-RW-	1015	Field 0x1015
ole-1016	-RW-	1016	Field 0x1016
ole-1017	-RW-	1017	Field 0x1017
ole-1018	-RW-	1018	Field 0x1018
ole-1019	-RW-	1019	Field 0x1019
ole-101a	-RW-	101a	Field 0x101a
ole-101b	-RW-	101b	Field 0x101b
ole-101c	-RW-	101c	Field 0x101c
ole-101d	-RW-	101d	Field 0x101d
ole-101e	-RW-	101e	Field 0x101e
ole-101f	-RW-	101f	Field 0x101f
ole-1020	-RW-	1020	Field 0x1020
ole-1021	-RW-	1021	Field 0x1021
ole-1022	-RW-	1022	Field 0x1022
ole-1023	-RW-	1023	Field 0x1023
ole-1024	-RW-	1024	Field 0x1024
ole-1025	-RW-	1025	Field 0x1025
ole-1026	-RW-	1026	Field 0x1026
ole-1027	-RW-	1027	Field 0x1027
ole-1028	-RW-	1028	Field 0x1028
ole-1031	-RW-	1031	Field 0x1031

Maker Note (Panasonic)

pn-quality	-RW-	0001	Image Quality
pn-0002	-RW-	0002	Field 0x0002
pn-white-bal	-RW-	0003	White Balance
pn-focus-mode	-RW-	0007	Focus Mode
pn-spot-mode	-RW-	000f	Spot Mode
pn-stab-mode	-RW-	001a	Image Stabiliser Mode
pn-macro-mode	-RW-	001c	Macro Mode
pn-shoot-mode	-RW-	001f	Shooting Mode
pn-audio	-RW-	0020	Audio Clip
pn-0021	-RW-	0021	Field 0x0021
pn-0022	-RW-	0022	Field 0x0022
pn-white-adj	-RW-	0023	White Balance Adjust
pn-flash-bias	-RW-	0024	Flash Bias
pn-0025	-RW-	0025	Field 0x0025
pn-0026	-RW-	0026	Field 0x0026
pn-0027	-RW-	0027	Field 0x0027
pn-color-effect	-RW-	0028	Color Effect
pn-0029	-RW-	0029	Field 0x0029
pn-002a	-RW-	002a	Field 0x002a
pn-002b	-RW-	002b	Field 0x002b
pn-contrast	-RW-	002c	Contrast
pn-noise-reduct	-RW-	002d	Noise Reduction
pn-002e	-RW-	002e	Field 0x002e
pn-002f	-RW-	002f	Field 0x002f
pn-4449	-RW-	4449	Field 0x4449

Maker Note (Pentax)

EXIFutils Command Reference

px-mode	-RW-	0001	Mode
px-prev-size	-RW-	0002	Preview Image Size
px-prev-len	-RW-	0003	Preview Image Length
px-prev-offset	-RW-	0004	Preview Image Offset
px-0005	-RW-	0005	Field 0x0005
px-0006	-RW-	0006	Field 0x0006
px-0007	-RW-	0007	Field 0x0007
px-quality	-RW-	0008	Quality
px-image-size	-RW-	0009	Image Size
px-zoom	-RW-	000a	Zoom
px-picture-mode	-RW-	000b	Picture Mode
px-000c	-RW-	000c	Field 0x000c
px-focus-mode	-RW-	000d	Focus Mode
px-000e	-RW-	000e	Field 0x000e
px-000f	-RW-	000f	Field 0x000f
px-0010	-RW-	0010	Field 0x0010
px-0012	-RW-	0012	Field 0x0012
px-0013	-RW-	0013	Field 0x0013
px-iso	-RW-	0014	ISO Setting
px-0015	-RW-	0015	Field 0x0015
px-meter-mode	-RW-	0017	Meter Mode
px-0018	-RW-	0018	Field 0x0018
px-white-bal	-RW-	0019	White Balance
px-001a	-RW-	001a	Field 0x001a
px-focal-len	-RW-	001d	Focal Length
px-zoom	-RW-	001e	Zoom
px-satur-comp	-RW-	001f	Saturation Compensation
px-contrast-comp	-RW-	0020	Contrast Compensation
px-sharp-comp	-RW-	0021	Sharpness Compensation
px-0022	-RW-	0022	Field 0x0022
px-0023	-RW-	0023	Field 0x0023
px-0024	-RW-	0024	Field 0x0024
px-0025	-RW-	0025	Field 0x0025
px-0026	-RW-	0026	Field 0x0026
px-0027	-RW-	0027	Field 0x0027
px-0028	-RW-	0028	Field 0x0028
px-0029	-RW-	0029	Field 0x0029
px-002b	-RW-	002b	Field 0x002b
px-002c	-RW-	002c	Field 0x002c
px-002d	-RW-	002d	Field 0x002d
px-0032	-RW-	0032	Field 0x0032
px-0033	-RW-	0033	Field 0x0033
px-0034	-RW-	0034	Field 0x0034
px-0035	-RW-	0035	Field 0x0035
px-0036	-RW-	0036	Field 0x0036
px-0037	-RW-	0037	Field 0x0037
px-003a	-RW-	003a	Field 0x003a
px-003d	-RW-	003d	Field 0x003d
px-003e	-RW-	003e	Field 0x003e
px-lens-id	-RW-	003f	Lens Id
px-0041	-RW-	0041	Field 0x0041
px-0047	-RW-	0047	Field 0x0047
px-0048	-RW-	0048	Field 0x0048
px-0049	-RW-	0049	Field 0x0049
px-004f	-RW-	004f	Field 0x004f
px-print-im	-RW-	0e00	Print IM
px-0200	-RW-	0200	Field 0x0200

EXIFutils Command Reference

px-0201	-RW-	0201	Field 0x0201
px-0202	-RW-	0202	Field 0x0202
px-0203	-RW-	0203	Field 0x0203
px-0204	-RW-	0204	Field 0x0204
px-0205	-RW-	0205	Field 0x0205
px-0206	-RW-	0206	Field 0x0206
px-0207	-RW-	0207	Field 0x0207
px-0208	-RW-	0208	Field 0x0208
px-0209	-RW-	0209	Field 0x0209
px-020a	-RW-	020a	Field 0x020a
px-020b	-RW-	020b	Field 0x020b
px-020d	-RW-	020d	Field 0x020d
px-020e	-RW-	020e	Field 0x020e
px-020f	-RW-	020f	Field 0x020f
px-0210	-RW-	0210	Field 0x0210
px-0211	-RW-	0211	Field 0x0211
px-0212	-RW-	0212	Field 0x0212
px-0213	-RW-	0213	Field 0x0213
px-0214	-RW-	0214	Field 0x0214
px-0215	-RW-	0215	Field 0x0215
px-0216	-RW-	0216	Field 0x0216
px-021f	-RW-	021f	Field 0x021f
px-03ff	-RW-	03ff	Field 0x03ff
px-time-zone	-RW-	1000	Time Zone
px-daylight-sav	-RW-	1001	Daylight Savings

Maker Note (Ricoh)

ro-0001	-RW-	0001	Field 0x0001
ro-0002	-RW-	0002	Field 0x0002
ro-0003	-RW-	0003	Field 0x0003
ro-0005	-RW-	0005	Field 0x0005
ro-0006	-RW-	0006	Field 0x0006
ro-1001	-RW-	1001	Field 0x1001
ro-1002	-RW-	1002	Field 0x1002
ro-2001	-RW-	2001	Camera Info Sub-IFD

Maker Note (Ricoh Camera Info)

ri-0001	-RW-	0001	Field 0x0001
ri-0002	-RW-	0002	Field 0x0002
ri-0003	-RW-	0003	Field 0x0003
ri-0005	-RW-	0004	Field 0x0005
ri-0006	-RW-	0006	Field 0x0006
ri-0007	-RW-	0007	Field 0x0007
ri-0008	-RW-	0008	Field 0x0008
ri-0009	-RW-	0009	Field 0x0009
ri-000a	-RW-	000a	Field 0x000a
ri-000b	-RW-	000b	Field 0x000b
ri-000c	-RW-	000c	Field 0x000c
ri-000d	-RW-	000d	Field 0x000d
ri-000e	-RW-	000e	Field 0x000e
ri-000f	-RW-	000f	Field 0x000f
ri-0010	-RW-	0010	Field 0x0010

8.7 Canon Raw (.CRW) Fields

----- Field Name -----	-Attr-	-Tag-	----- Description -----
crw-date	-R--	0000	Date/Time Taken

EXIFutils Command Reference

crw-file-format	-R--	0178	File Format
crw-owner	-R--	01d2	Owner
crw-vendor	-R--	01f2	Vendor
crw-model	-R--	01f8	Camera Model
crw-firm-ver	-R--	0212	Firmware Version
crw-serial-num	-R--	0236	Camera Serial Number
crw-iso	-R--	0288	ISO Setting
crw-shutter	-R--	02b0	Shutter Speed
crw-aperture	-R--	02ae	Aperture (F-stop)
crw-creative-mode	-R--	02e2	Creative Mode
crw-autofocus-mode	-R--	02c8	Autofocus Mode
crw-meter-mode	-R--	02dc	Meter Mode
crw-photo-in-seq	-R--	0296	Photo no. in Sequence
crw-bulb-duration	-R--	02b4	Bulb Duration
crw-shutter-delay	-R--	02be	Shutter Delay
crw-drive-mode	-R--	02c4	Drive Mode
crw-white-point	-R--	0292	White Point
crw-exp-comp	-R--	0290	Exposure Compensation
crw-focus-lower	-R--	02aa	Focus Distance Lower (m)
crw-focus-upper	-R--	02ac	Focus Distance Upper (m)
crw-zoom-lower	-R--	02e8	Zoom Range Lower (mm)
crw-zoom-upper	-R--	02ea	Zoom Range Upper (mm)
crw-focal-len-used	-R--	152e	Focal Length Used
crw-flash-comp	-R--	02a2	Flash Compensation (EV)
crw-param-contrast	-R--	02d4	Contrast (parameter)
crw-param-saturation	-R--	02d6	Saturation (parameter)
crw-param-sharpness	-R--	02d8	Sharpness (parameter)
crw-param-tone	-R--	030e	Color Tone (parameter)
crw-flash-mode	-R--	02c2	Flash Mode
crw-orient	-R--	15f4	Orientation
crw-rotation	-R--	000c	Rotation (degrees)
crw-aeb-seq	-R--	02a4	AE Bracket Sequence
crw-aeb-value	-R--	02a6	AE Bracket Value (EV)
crw-custom-2	-R--	0f1c	Custom Field 2
crw-custom-3	-R--	0f1e	Custom Field 3
crw-custom-4	-R--	0f20	Custom Field 4
crw-custom-5	-R--	0f22	Custom Field 5
crw-custom-6	-R--	0f24	Custom Field 6
crw-custom-7	-R--	0f26	Custom Field 7
crw-custom-8	-R--	0f28	Custom Field 8
crw-custom-9	-R--	0f2a	Custom Field 9
crw-custom-10	-R--	0f2c	Custom Field 10
crw-custom-11	-R--	0f2e	Custom Field 11
crw-custom-12	-R--	0f30	Custom Field 12
crw-custom-13	-R--	0f32	Custom Field 13
crw-custom-14	-R--	0f34	Custom Field 14
crw-custom-15	-R--	0f36	Custom Field 15

EXIFutils Command Reference

8.8 IPTC Fields

Refer to Section 8.1 for an explanation of the field information shown here.

----- Field Name -----	-Attr-	-Tag-	----- Description -----
IPTC 1: Addressing			
ip1-version	-RWS	1.000	Dataset 1 Record Version
ip1-destination	-RWS	1.005	Destination
ip1-format	-RWS	1.020	File Format
ip1-format-ver	-RWS	1.022	File Format Version
ip1-service-id	-RWS	1.030	Service Identifier
ip1-env-num	-RWS	1.040	Envelope Number
ip1-product-id	-RWS	1.050	Product ID
ip1-env-pri	-RWS	1.060	Envelope Priority
ip1-date-sent	-RWS	1.070	Date Sent
ip1-time-sent	-RWS	1.080	Time Sent
ip1-char-set	-RWS	1.090	Coded Character Set
ip1-uno	-RWS	1.100	Unique Name of Object
ip1-arm-id	-RWS	1.120	ARM Identifier
ip1-arm-ver	-RWS	1.122	ARM Version
IPTC 2: Editorial			
ip-version	IRWS	2.000	Dataset 2 Record Version
ip-obj-type-ref	IRWS	2.003	Object Type Reference
ip-obj-attr-ref	IRWS	2.004	Object Attribute Reference
ip-object	IRWS	2.005	Object
ip-edit-status	IRWS	2.007	Edit Status
ip-editor-update	IRWS	2.008	Editorial Update
ip-urgency	IRWS	2.010	Urgency
ip-subj-ref	IRWS	2.012	Subject Reference
ip-category	IRWS	2.015	Category
ip-suppcat	IRWS	2.020	Supplemental-Categories
ip-fixture	IRWS	2.022	Fixture
ip-keyword	IRWS	2.025	Keywords
ip-cont-loc-code	IRWS	2.026	Content Location Code
ip-cont-loc-name	IRWS	2.027	Content Location Name
ip-rel-date	IRWS	2.030	Release Date
ip-rel-time	IRWS	2.035	Release Time
ip-exp-date	IRWS	2.037	Expiration Date
ip-exp-time	IRWS	2.038	Expiration Time
ip-instructions	IRWS	2.040	Special Instructions
ip-action-advised	IRWS	2.042	Action Advised
ip-ref-service	IRWS	2.045	Reference Service Ident.
ip-ref-date	IRWS	2.047	Reference Date
ip-ref-env-num	IRWS	2.050	Reference Envelope Number
ip-date	IRWS	2.055	Creation Date
ip-time	IRWS	2.060	Creation Time
ip-digi-date	IRWS	2.062	Digital Creation Date
ip-digi-time	IRWS	2.063	Digital Creation Time
ip-program	IRWS	2.065	Originating Program
ip-prog-ver	IRWS	2.070	Program Version
ip-obj-cycle	IRWS	2.075	Object Cycle
ip-byline	IRWS	2.080	Byline
ip-byline-title	IRWS	2.085	Byline Title
ip-city	IRWS	2.090	City
ip-subloc	IRWS	2.092	Sub Location

EXIFutils Command Reference

ip-state-prov	IRWS	2.095	State/Province
ip-loc-code	IRWS	2.100	Location Code
ip-country	IRWS	2.101	Country
ip-orig-ref	IRWS	2.103	Original Xmit Reference
ip-headline	IRWS	2.105	Headline
ip-credit	IRWS	2.110	Credit
ip-source	IRWS	2.115	Source
ip-copyright	IRWS	2.116	Copyright Notice
ip-contact	IRWS	2.118	Contact
ip-caption	IRWS	2.120	Caption
ip-local-caption	IRWS	2.121	Local Caption
ip-cap-writer	IRWS	2.122	Caption Writer
ip-image-type	IRWS	2.130	Image Type
ip-image-orient	IRWS	2.131	Image Orientation
ip-lang-id	IRWS	2.135	Language Id
ip-audio-type	IRWS	2.150	Audio Type
ip-audio-samp-rate	IRWS	2.151	Audio Sampling Rate (Hz)
ip-audio-samp-res	IRWS	2.152	Audio Sampling Resolution
ip-audio-duration	IRWS	2.153	Audio Duration
ip-audio-outcue	IRWS	2.154	Audio Outcue
ip-job-id	IRW-	2.184	Jod Id
ip-master-doc-id	IRW-	2.185	Master Document Id
ip-short-doc-id	IRW-	2.186	Short Document Id
ip-unique-doc-id	IRW-	2.187	Unique Document Id
ip-owner-id	IRW-	2.188	Owner Id
ip-preview-format	IRWS	2.200	Preview File Format
ip-service-id	IRWS	2.201	Service Id
ip-class-state	IRW-	2.225	Classification State
ip-sim-index	IRW-	2.228	Similarity Index
ip-doc-notes	IRW-	2.230	Document Notes
ip-doc-history	IRW-	2.231	Document History
ip-exif-info	IRW-	2.232	Camera EXIF Information

IPTC 3: Newsphoto Parameters

ip3-version	-RWS	3.000	Dataset 3 Record Version
ip3-picture-num	-RWS	3.010	Picture Number
ip3-width	-RWS	3.020	Image Width
ip3-height	-RWS	3.030	Image Height
ip3-pix-size-scan	-RWS	3.040	Pixel Size - Scan Dirctn
ip3-pix-size-perp	-RWS	3.050	Pixel Size - Perpedicular
ip3-supp-type	-RWS	3.055	Supplemental Type
ip3-color-rep	-RWS	3.060	Color Representation
ip3-color-space	-RWS	3.064	Interchange Color Space
ip3-color-seq	-RWS	3.065	Color Sequence
ip3-index-entries	-RWS	3.084	Number of Index Entries
ip3-bits-per-sample	-RWS	3.086	Bits per Sample
ip3-sample-struct	-RWS	3.090	Sample Structure
ip3-scan-dir	-RWS	3.100	Scanning Direction
ip3-rotation	-RWS	3.102	Image Rotation (degrees)
ip3-data-comp	-RWS	3.110	Data Compression Method
ip3-quant-method	-RWS	3.120	Quantization Method
ip3-end-points	-RWS	3.125	End Points
ip3-excursion	-RWS	3.130	Excursion Tolerance
ip3-bits-per-comp	-RWS	3.135	Bits per Component

IPTC 7: Subfile Size

ip7-size-mode	-RWS	7.010	Size Mode
---------------	------	-------	-----------

EXIFutils Command Reference

ip7-max-subfile	-RWS	7.020	Max Subfile Size
ip7-obj-size	-RWS	7.090	Object Size Announced
Photoshop			
ip-copyrighted	-RW-	-----	Mark as Copyrighted
ip-url	-RW-	-----	Image URL

8.9 Ricoh RMETA Fields

----- Field Name -----	-Attr-	-Tag-	----- Description -----
rc-name1	-R--	0001	Custom Field 1 Name
rc-value1	-R--	0001	Custom Field 1 Value
rc-name2	-R--	0002	Custom Field 2 Name
rc-value2	-R--	0002	Custom Field 2 Value
rc-name3	-R--	0003	Custom Field 3 Name
rc-value3	-R--	0003	Custom Field 3 Value
rc-name4	-R--	0004	Custom Field 4 Name
rc-value4	-R--	0004	Custom Field 4 Value
rc-name5	-R--	0005	Custom Field 5 Name
rc-value5	-R--	0005	Custom Field 5 Value

9 Software License Agreement

Carefully read this license agreement before using the product. Using the product indicates that you have read this license agreement and agree to its terms.

By using the product you accept the following License Agreement. If you do not agree to the conditions of this license, delete the product from your system.

Unregistered User License: The Unregistered User License entitles you to use a restricted set of product functionality for an unlimited time on any single computer without purchasing a license key. The software is in use when it is either loaded into RAM or installed into the hard disk or other permanent memory. The product functionality provided by the Unregistered User license is described in the Users Guide.

Registered User License: To use the full functionality of the product a Registered User license must be purchased. Installing the Registered User license key enables the full functionality of the product for an unlimited time. A Registered User license permits you to use one copy of the software included in this package on any single computer. For each software license, the program can be in use on only one computer at any given time. The software is in use when it is either loaded into RAM or installed into the hard disk or other permanent memory.

The software is protected by United States copyright laws, international treaty provisions, and all other applicable national laws. The software must be treated like all other copyrighted materials (e.g. books and musical recordings).

OTHER RESTRICTIONS. This License Agreement is your proof of license to exercise the rights granted herein and must be retained by you. LICENSEE may not rent or lease the Product. LICENSEE may not reverse engineer, decompile or disassemble the software program except to the extent such foregoing restriction is expressly prohibited by applicable law.

NO WARRANTY. ANY USE BY LICENSEE IS AT THE LICENSEE'S OWN RISK. PRODUCT IS PROVIDED FOR USE "AS IS" WITHOUT WARRANTY OF ANY KIND. TO THE MAXIMUM EXTENT PERMITTED BY LAW, THE AUTHOR DISCLAIMS ALL WARRANTIES OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. THE AUTHOR IS NOT OBLIGATED TO PROVIDE ANY UPDATES TO THE PRODUCT.

NO LIABILITY FOR CONSEQUENTIAL DAMAGES. In no event shall the author be liable for any damages whatsoever (including, without limitation, incidental, direct, indirect and consequential damages, damages for loss of business profits, business interruption, loss of business information, or other pecuniary loss) arising out of the use or inability to use this product, even if advised of the possibility of such damages. Because some states/countries do not allow the exclusion or limitation of liability for consequential or incidental damages, the above limitation may not apply to you.

This shareware software may be freely distributed, provided that; (1) Such distribution includes only the original archive. You may not alter, delete or add any files in the distribution archive. (2) The distribution does not include a registration key. (3) No money is charged to the person receiving the software, beyond reasonable cost of packaging and other overhead.

10 Version History

10.1 Version 2.7

10.1.1 New Features

- Add "read only" support for EXIF fields in Encapsulated Postscript (.eps) files.
- Add support for Ricoh Maker Note fields
- Add read only support for Ricoh RMETA Custom Fields (created by Ricoh Ricoh Pro G3 GPS-capable camera).
- Improved support for non-ASCII character sets:
 - Add support for viewing and editing Windows XP specific UNICODE fields.
 - Added /u option to exifedit to specify that EXIF Comment fields are to be stored in UNICODE (previous only ASCII comments were supported).
 - The /p option has been added to set the character sets used to interpret EXIF and IPTC text fields. Environment variables can also be used to specify characters sets.
 - Added /i option to exiflist, to display the character sets being used.
- Add support for XP Digital Image Pro Tags field (0x4747)
- Increase max length of ip-keyword field from 32 to 1999 characters.
- Add list of defined values for IPTC Coded Character Set field (1:90), nickname ip1-char-set.
- If the demoninator of the exp-time value is not a whole number to two decimal places, then display it's value to two decimal places.

10.1.2 Bug Fixes

- Fix bug where two fields had the same nickname (n3-color-mode). Second occurrence of the field was renamed to n3-color-mode2.
- Make handling of invalid 'next IFD' offset pointers more robust. In previous versions invalid offset pointers cause a "too many format errors" message and resulted in incomplete EXIF data.
- Fix bug in handling of TIFF strip offsets and lengths with datatype SHORT.
- Fix bug in exiflist -t option that caused extracted thumbnail to be incorrect for some Nikon images. The problem occurred when there were two thumbnails in the image, one of which was in the Nikon Maker note.
- Rename "Nikon NEF Thumbnail" IFD to "Nikon Thumbnail" as this IFD can also appear in JPEG files.
- Fix bug in editing files containing Thumbnails embedded in Nikon Maker Notes
- Fix bug that caused incorrect values to be set when IPTC values were being both set and used as template values in the same exifedit command.
- Improve validation of command arguments containing "@" file input as invalid values could cause the program to crash.

10.2 Version 2.6

- Canon Raw (.CRW and .CR2) files now supported by `exiflist`, `exifcopy`, and `exiffile`.
- Improved support for model-specific fields (Maker Notes)
 - Panasonic Maker Notes now supported
 - Konica Minolta branded cameras now supported
 - Pentax Maker Note Lens Id field (px-lens-id) now supported.
- Can now reference individual parts of the Date Taken EXIF field using the following new nicknames:
 - `yyyy` - 4 digit year
 - `yy` - 2 digit year
 - `mm` - 2 digit month
 - `mmm` - 3 letter month (eg. Jan)
 - `hr` - 2 digit hour (24 hour clock)

EXIFutils Command Reference

- min - 2 digit minutes
- sec - 2 digit seconds
- o Improved GPS support. GPS seconds values to be specified to 2 decimal places (previously only integer whole numbers of seconds were accepted).
- o Add support for more iptc fields:

Field Name	Attr	Tag	Description
ip-local-caption	IRWS	2.121	Local Caption
ip-job-id	IRW-	2.184	Jod Id
ip-master-doc-id	IRW-	2.185	Master Document Id
ip-short-doc-id	IRW-	2.186	Short Document Id
ip-unique-doc-id	IRW-	2.187	Unique Document Id
ip-owner-id	IRW-	2.188	Owner Id
ip-class-state	IRW-	2.225	Classification State
ip-sim-index	IRW-	2.228	Similarity Index
ip-doc-notes	IRW-	2.230	Document Notes
ip-doc-history	IRW-	2.231	Document History
ip-exif-info	IRW-	2.232	Camera EXIF Information
- o Binary fields can now be edited.
- o Bug fixes
 - Ensure padding bytes in IPTC data are zeroed, as Photoshop does not accept non-zero padding.
 - Fix error in exifdate usage text
 - Fix detection of EXIF data in Minolta raw (.MRF) files from Minolta 7D SLR
 - Fix double processing of renamed files in exiffile when run on WindowsXP.
 - Fix handling of EXIF thumbnails in TIFF, NEF, and .DCR files.

10.3 Version 2.5

10.3.1 exifedit

- Edit IPTC fields, and copy field values between IPTC fields and EXIF fields (and vice versa)
- exifedit can now process all files in a directory tree. Previously could only process all files in a single directory.
- Setting date/time field made simpler. Previously you had to specify the date time in exactly the right format. Now exifedit will accept a number of different date formats and will automatically convert to the required format. Also, if a date is specified when I date/time is required, the time will automatically be set to 00:00:00.
- EXIF data/time values can be assigned to IPTC date/time fields (and vice versa) and the value will automatically be converted to the correct format.
- can now individually remove all EXIF, IPTC, or Flashpix audio data from an image
- In field/value lists, field values containing spaces no longer need to be enclosed in quotes. For example, the following is now valid:

```
exifedit -a "date-taken=2004:03:31 12:13:00" myphoto.jpg
```

in previous versions an additional set of quotes was required:

```
exifedit -a "description=\"2004:03:31 12:13:00\"" myphoto.jpg
```
- -j option added. Specifies the separator character to use between repeating IPTC fields (eg ip-keyword and ip-suppcat)

10.3.2 exiflist

- Limit on size of template file removed (previously the maximum was 10,000 bytes; it si now limited only by available memory).
- IPTC fields now included in .exi files created with the -e option
- -n option added. Specifies the character with which to replace new line characters in output values.
- -t -w -e can now be used in conjunction with -r to extract thumbnails, audio data, and meta data from all files in a directory tree.

EXIFutils Command Reference

- -j option added. Specifies the separator character to use between repeating IPTC fields (eg ip-keyword and ip-suppcat)

10.3.3 exifcopy

- When copying between JPEG files, Flashpix and IPTC fields now copied (previously only EXIF data was copied).

10.3.4 Miscellaneous

- Minor corrections to Minolta Maker Note fields
- Add TIFF Document Storage and Retrieval tags
- Pentax Maker Notes now supported.
- Maker notes formats for major brands now automatically detected

10.3.5 Bug Fixes

- Editing TIF files that contained a single strip thumbnail caused an invalid TIF file to be generated
- GPS latitude and longitude values were incorrectly being treated as signed values instead of unsigned.
- Windows XP related issues
 - WINDIR not defined on all WindowsXP systems. Use SYSTEMROOT instead.
 - When processing all files in a directory using exifedit or exifcopy, on some systems the command would processed generated backup files in a directory

10.4 Version 2.4

The following new features have been introduced in V2.4:

- Additional file types supported
 - **Minolta Raw (.MRW) files:** All EXIF fields can be listed. The entire EXIF data block can be copied into a JPEG file or into an EXIF .EXI file. Selected EXIF fields can be copied to any other image file type. Minolta Raw files cannot be edited.
 - **Fujifilm Raw (.RAF) files:** All EXIF fields can be listed. Selected EXIF fields can be copied to any other image file type. Fujifilm Raw files cannot be edited.
 - **EXIF .EXI files:** .EXI files are used to backup EXIF information from other image file for later return after the image has been edited. Using the `exiflist -e` option, all EXIF data can be extracted from a .JPG, .MRW, or .RAF file and stored in a .EXI file. EXIF information in a .EXI file can then be copied into any other image file using `exifcopy`. The .EXI files created by EXIFutils are compatible with those created by the `exifer` application (www.friedemann-schmidt.com/software/exifer).
- Improved Maker Note support
 - Support for Canon Maker Note fields greatly improved. In earlier versions of EXIFutils many Canon Maker note values were combined into two fields "Settings 1" and "Settings 4". All Canon Maker note fields can now be individually selected and displayed.
 - Most Minolta Maker Note fields are now interpreted (previously the meaning of most fields was unknown).
 - Maker Notes for the following cameras are now supported:
 - Canon Powershot S45, S50, A300, A60, A70, G3, G5, S400, SD100, 10D, Digital Rebel.
 - Casio EX-Z3, EX-S3, QV-5700, QV-R40
 - Fujifilm FinePix A205, A210, A310, F410, S5000
 - Minolta DiMAGE 7Hi, Xi, Xt, Z1, A1, F300
 - Nikon E3100, E5400, SQ
 - Olympus C750UZ, X200, D560Z, C350Z, u10D, S300D, u300D, u20D, S400D, u400D.
- More IPTC fields now supported. 56 more IPTC fields can now be displayed, include fields from Dataset 1 (Addressing), Dataset 2 (Editorial), and Dataset 7 (Subfile Size).
- Additional image file attributes available as fields for use in output and templates:
 - `file-date-mod` - Date the file was last modified
 - `file-date-created` - Date the file was created (Windows only)

EXIFutils Command Reference

- `file-name-exi` - Default name of the `.exi` file created by `exiflist -e` option.
- The User Guide has been split into three separate documents:
 - A Getting Started Guide, which describes concepts common to all EXIFutils commands, and explains common scenarios in which EXIFutils can be used.
 - A Command Reference Manual, which describes in detail the features provided by each EXIFutils command.
 - A Field Reference Guide, which list all EXIF, IPTC, and file attributes fields that can be used by EXIFutils.

The following problems have been fixed:

- General
 - Absolute path name in thumbnail template did not work on Windows (“C:\” was translated to”C-”).
 - Handling of incorrectly formatted IPTC fields made more fault tollerant.
 - Spurious characters appended to some character strings when displayed.
 - On Windows, the `/?` option was not being recognized. It is now produces usage information (the same as `/h`).
- `exifcopy`
 - spaces in file names not handled when `-f` option used
- `exifdate`
 - When adding or subtracting a date/time value, the addition/subtraction was applied to the date-modified field twice.
- `exifedit`
 - When adding a large thumbnail image using the `-t a` option, a corrupt EXIF data block was created if the thumbnail image was too large to fit in the EXIF block. An error message is now displayed if the thumbnail is too large.
- `exifkey`
 - A Sementation Fault occurred if the license file could not be read.
 - Trailing space characters in the username or email address caused `exifkey` to hang.
- `exiflist`
 - The `ip-image-type` and `ip-lang-id` field were not being displayed even if they were present.
 - When using list output (`-o l...` option) field value strings containing the separator character were not being quoted

10.5 Version 2.3

Command	Feature	Description	For more information see
General	EXIF V2.2	EXIF 2.2 fields are now supported (previously only EXIF V2.1 fields were supported)	
	IPTC fields	IPTC (International Press Telecommunications Council) fields can now be displayed.	
	Improved Maker Note supported	Added support for the following cameras: <ul style="list-style-type: none"> ○ Olympus C5050Z, ○ Fujifilm FinePix F401, ○ Minolta DiIMAGE F100, ○ Nikon D1, ○ Canon G1, ○ Canon G2 Improved support for Nikon Type 3 Maker Notes	

EXIFutils Command Reference

	New file-related nicknames	Additional file attribute nicknames have been defined: <ul style="list-style-type: none"> o file-ext (file name extension) o file-base (file base name) o file-name-thumb (file name of extracted thumbnail) o file-name-audio (file name of extracted audio stream) o file-name-backup (name of backup file to be created) 	
	Nicknames case insensitive	Nicknames can now be entered in both upper and lower case (in V2.2 nicknames had to be entered in lower case)	
exiflist	New, flexible output format	In addition to predefine output formats, <i>exiflist</i> now supports output based on a user-defined <i>template</i> file.	Section 6 “Templates”.
	Can specify name/dir of thumbnail to be created	When extracting the embedded thumbnail image using the <i>-t</i> option, the user can now specify the name of the extracted file, and the directory into which it is written.	Section 7.6.3 “Thumbnail Image Extraction”
	Can specify name/dir of WAV file to be created	When extracting the embedded audio stream using the <i>-w</i> option, the user can now specify the name of the extracted file, and the directory into which it is written.	Section 7.6.5 “Audio Stream Extraction”
exifedit	Set fields based on the value of other fields	The value to which a field is set can now be specified as a <i>template</i> that includes the values of other fields.	Section 6 “Templates”. Section 7.3 “EXIFEDIT”
exiffile	Rename files based on field values	exiffile has a new <i>-n</i> option, which renames images files based on the values of other EXIF, IPTC, and field attribute nicknames.	Section 7.4.1.1 “Renaming Files”
exifcopy	exifcopy <i>-f</i> now works for JPG-JPG copies	It is now possible to copy individual fields from one JPG file to another JPG file (previously all fields were copied)	Section 7.1.1.2 “Supported Image File Types”

The following problems have been fixed:

- General
 - o /r not handled correctly in string fields
 - o Temporary files were sometimes created in the current working directory in which the program was run, instead of being created in the same dir as the file being edited/copied to.
 - o Some Olympus and Minolta Maker Note field definitions were incorrect, causing warning messages to be erroneously displayed.
- exiflist
 - o String values were not wrapped correctly when last character on the line was white space.
 - o Random text appended to the end of some strings output values.
 - o file-name nickname interpreted as file-name-full in SQL output
 - o Directory name incorrectly included in the file-name field when a path was included on command line
 - o exiflist reported shutter speeds written by exifedit as a power of 2 lower than the correct value.
- exifedit
 - o Generated Backup file names and thumbnail file names not correct when dash '.' was the first character of the file name
 - o Multiple APP1 markers in an JPG file caused EXIFEDIT to generate a corrupt JPG file.
 - o exifedit incorrectly formats FUJIFILM Maker Notes field for some Fujifilm models.

EXIFutils Command Reference

- Temporary thumbnail files were not always deleted
- exifcopy
 - File names starting with a dash '-' not handled correctly by exifcopy (UNIX only)

10.6 Version 2.2

GENERAL

1. Added Maker Note support for the following makes/models:
 - Canon PowerShot S20
 - Canon PowerShot Pro90 IS
 - Casio QV-3000EX
 - Casio QV-3EX
 - Casio QV-4000
 - Epson PhotoPC 3000Z
 - Epson PhotoPC 3100Z
 - Fujifilm FinePix F601 ZOOM
 - Fujifilm FinePix S602 ZOOM
 - Fujifilm FinePix 4700 ZOOM
 - Fujifilm FinePix 4800 ZOOM
 - Fujifilm FinePix 4900 ZOOM
 - Fujifilm FinePix 6800 ZOOM
 - Fujifilm FinePix 6900 ZOOM
 - Fujifilm FinePix S2 Pro
 - Minolta DiMAGE 5
 - Minolta DiMAGE 7i
 - Nikon E880
 - Nikon E885
 - Nikon E995
 - Nikon E5000
 - Nikon E4500
 - Nikon E5700
 - Nikon D1H
 - Nikon D100
 - Olympus C3000Z
 - Olympus C300Z
 - Olympus D550Z
 - Olympus C3030Z
 - Olympus C3040Z
 - Olympus C3100Z
 - Olympus C3020Z
 - Olympus C4040Z
 - Olympus C40Z
 - Olympus C720UZ
 - Olympus E-10
2. Fix minor EXIF specification conformance issues:
 - a. exiflist assumed first IFD always started at offset 8. It now correctly determines the offset to the EXIF data.
 - b. User Comment field was sometimes not placed in field tag order within the EXIF data
 - c. Related Sound File field was incorrectly defined as variable length. Correct definition is as a 12 character fixed length field.
 - d. EXIF data type 13 (IFD offset) now supported.
3. Add definitions for Windows XP specific fields.

EXIFEDIT

1. exifedit can now add EXIF data to an image file that did not contain EXIF data (previously exifcopy had to be used to add EXIF data to a file before exifedit could be used to edit the fields). If exifedit is used

EXIFutils Command Reference

with the `'/a'`, `'/s'`, or `'/t a'` options, and the file does not contain any EXIF data, then `exifedit` will create a basic EXIF structure before adding the specified fields.

2. Added `/e` option to remove all EXIF data from the image file (i.e. all APP1 EXIF data blocks and all APP2 FlashPix Extension data blocks will be deleted).
3. Add `/t a,@filename` option to replace thumbnail image with a user-supplied JPEG thumbnail image.

EXIFLIST

1. Added `/w` option to extract embedded EXIF audio data into a separate `.wav` audio file.
2. Added `/k` option to allow user to specify an alternative quote character for `/o ln` format output.
3. Fixed bugs in escaping of quote characters:
 - a. In `'/o ln'` format output, double quotes characters (`"`) were not preceded by the escape character when they occurred within field values
 - b. In SQL format output, an escape character did not precede single quote characters when they occurred within field values.
4. In SQL format output, all string field values should be surrounded by quote characters. This was not being done for all fields.

10.7 Version 2.1

EXIFEDIT

- 1) Added improved thumbnail generation. The `/t` option can now be specified in three different forms:
 - `/t a` - generate a thumbnail that is 160x120 pixels
 - `/t a,size` - generate a thumbnail that has its longest dimension 'size' pixels long, with the length of the shorter side scaled to maintain the image aspect ratio, eg `/t a,300`
 - `/t a,wwwxhhh` - generate a thumbnail that is www pixels wide and hhh pixels high, eg `/t a,300x200`

10.8 Version 2.0

GENERAL

1. First Shareware version.
2. Added support for TIFF files. Other file formats based on the TIFF standard may also work
3. Can copy/merge fields between JPG and TIFF files or between two TIFF files.
4. New utility `EXIFFILE` that sets the JPG or TIFF file's last modified date to the date the photo was taken.
5. Increase maximum number of fields that can be specified (for listing or edit) to 200 (was previously 20).
6. Add proper installation process added (Windows version only)
7. Use Guide now included.
8. Add support for more Maker Note fields:
 - a. Olympus E-20, E20-N, E-20P
 - b. Canon PowerShot S40
 - c. Canon PowerShot A20
 - d. Nikon D1X
 - e. Epson PhotoPC 850Z
 - f. Minolta DiIMAGE 7
9. Windows version now accepts UNIX-style command options i.e. option parameters can start with `'-'` instead of `'/'`. For example, both of the following are now valid in the Windows version:
 - `exiflist /o l /f file-name,date-taken .`
 - `exiflist -o l -f file-name,date-taken .`

EXIFLIST

1. Added support for more Canon Make Note fields (Quality, Digital Zoom, Focus Type, Flash Activity).
2. Unknown fields are now printed in the IFD in which they are found rather than being listed together at the end.

EXIFutils Command Reference

3. File Source and Scene Type now interpreted correctly.
4. Added the /o lf and /o ln options /l option now requires a suboption. Valid values are '/l n' (list field names - this is what /l alone did in V1.5), '/l f' (print a full list of fields and details of valid field values to be used when editing, '/l field-name-list' (similar to '/l f' but only prints details for selected fields.
5. Can now use wildcards when specifying fields in the /f option.
6. Can now specify /f exif-common to select all common EXIF fields
7. Fix bug which caused an extra comma to be included at the end of the heading line when /o lh option used.

EXIFEDIT

1. Can now add/replace/delete most fields. See 'exiflist /l f' command for a complete list of the fields that are now editable.
2. Can automatically adjust the width and height fields to match the actual image size
3. Fix buffer overrun problem if field value longer than maximum
4. Bug fix: Editing EXIF data that contained GPS information caused invalid EXIF data to be written.
5. Added '/t a' to regenerate thumbnails

EXIFCOPY

1. /m option will now accept a match length of zero, which means that all destination files will match.
2. Can now copy selected fields to/from tiff files.
3. Incompatibilities:
 - a. -f changed to -o
 - b. backup files now suffixed with -be instead of -nx

10.9 Version 1.5

GENERAL

1. Fixed bug in handling of EXIF data larger than 2KB.

EXIFLIST

2. Added /t option, which extract the thumbnail image from the EXIF data into a separate file.
3. Added support for Global Positioning System (GPS) fields
4. Added support for reading field list (/f option) from standard input
5. Added support for the following Maker Note Fields
 - a. Olympus C2500L
 - b. Fujifilm
 - c. Minolta DiMAGE 7 (basic support only)
 - d. - Nikon D1X (basic support only)"Basic support" means that the field values are displayed, but the names and meanings of the fields are not known

EXIFEDIT

1. Added support for reading field lists (/a /r options) from standard input
2. "/t" option changed to "/t r" in preparation for adding more thumbnail actions (add thumbnail is planned)
3. Fixed bug in generation of Maker Note fields. This bug caused some EXIF display programs to fail to displaying Make Note fields (see below for more details).
4. Fixed bug in order of generated EXIF fields. The EXIF structure written by EXIFEDIT did not conform to the EXIF standard in that fields were not order in ascending order by field tag. As far as I know this error did not cause any problems, but it has now been corrected so that the fields are written in the order required by the EXIF Specification.
5. There was a bug in the generation of Maker Note fields which caused the Maker Note tag to have a data type of UNSIGNED LONG and a length of 1. It should have had a data type of UNDEFINED and the length set to the length of the Make Note data. This error caused some EXIF display programs to fail to

EXIFutils Command Reference

display make note fields created by EXIFEDIT. If you have encountered this problem you can fix the Make Note field by editing the EXIF data again using this new version of EXIFEDIT.

10.10 Version 1.4

GENERAL

1. Added support for Canon ShowerShot Maker Note
2. Minor corrections to field definitions in Casio Maker Note
3. Removed most warnings when compiling on VC6

EXIFLIST

1. Maximum display size for field values increases from 300 to 500 bytes
2. Long field values now wrap at a punctuation mark instead of at maximum line length.

10.11 Version 1.3

GENERAL

1. First production release of EXIFEDIT (a Beta release was included in EXIFutils V1.2)

EXIFLIST

1. Now supports Nikon E990 Maker Note.
2. The meaning of the "file-name" pseudo-field has been changed. In previous versions it contained the full file path and file name. It now contains only the file name. To get the path see the file-name-full and file-dir pseudo-fields described below.
3. Two new pseudo-fields have been added:
 - a. file-name-full - the full path and file name to the file.
 - b. file-dir - the directory in which the file was found.
4. Support for the following string fields added:
 - a. image-history
 - b. artist

NOTE: I'm not sure how "standard" these fields are. The EXIF documentation lists them under "miscellaneous fields". If the display program you are using does not support these fields then it should ignore them.

EXIFEDIT

1. Support for the following string fields added:
 - a. image-history
 - b. artist

NOTE: I'm not sure how "standard" these fields are. The EXIF documentation lists them under "miscellaneous fields". If the display program you are using does not support these fields then it should ignore them.

10.12 Version 1.2

GENERAL

1. Windows version now built using Visual C++ V6.0
2. Added EXIFEDIT utility, which adds and removes EXIF fields.

EXIFLIST

1. Now supports text fields up to 200 characters long (previously truncated text fields to 52 characters).
2. Added support for ASCII User Comment fields (previously the User Comment was displayed as an unformatted hexadecimal string).

EXIFutils Command Reference

3. Added support for the following new fields:
 - a. sub-time
 - b. sub-time-orig
 - c. sub-time-digi
 - d. cfa-pattern
4. Added support for the Maker Note field for the following cameras:
 - a. Olympus D-450Z and C-920Z
 - b. Nikon E700, E800, E900, E900S, E910, E950
 - c. Casio QV-2000UX and QV-8000SXNote that the meaning of some fields is now known. For these fields the value is display in raw format (see /u option on EXIFLIST command).

10.13 Version 1.1.1

No functional changes. Source code changed so that the Windows version will compile using Visual C++ V6.0 (previously Windows version was built using GCC).

10.14 Version 1.1

GENERAL

1. Added EXIFCOPY utility, which copies EXIF data from one JPEG file to another.
2. Fixed bug in JPEG/EXIF file decoding routines, which could have caused buffer overruns

EXIFLIST

1. Add "/f @file-name" option, which allows the list of display fields to be read from a text file. This is used to avoid command line length limitations, which occur when large numbers of fields are specified.
2. Added definitions for additional Interoperability field, and
3. changed the following field nicknames:
4. r98-index -> iop-index
5. r98-ver -> iop-ver

10.15 Version 1.0

EXIFDATE

Fix bug which caused exifdate to incorrectly change date fields in JPEG files that have been manipulated with 'JPEG Wizard', 'ThumbsPlus', 'ACDsee', and any other image manipulation utilities that do not save the EXIF Marker as the first marker in the file.

10.16 Version 0.5

GENERAL

1. Fix field value display routines to remove redundant blank that was present after some values
2. Fix bug in JPEG file decode routines, which did not correctly handle very short files.
3. Improve robustness of EXIF decode routines so that they are more tolerant of badly formatted EXIF fields.
4. Tidied up sources to be more compatible with VC++ (renamed ERROR #define to EXIF_ERR, and renamed WINDOWS #define to WIN32)

EXIFLIST

1. Added /f option to allow user to select which fields get displayed in list mode and sql mode.

EXIFutils Command Reference

2. Added file size (in bytes) as a field value that can be displayed in list mode and sql modes.
3. Add '/o lh' option to allow the user to select whether a heading row is printed in list mode ('/o lh' is equivalent to '/o l' in V0.4)
4. Add /l option to provide list of valid field names that can be specified in the /f option.
5. Added /v option to show program version information

EXIFDATE

1. Added /v option to show program version information

10.17 Version 0.4

Fix bug which caused EXIFLIST to erroneously report that there was no EXIF data in a JPEG file. This occurred when the image had been manipulated with 'JPEG Wizard', 'ThumbsPlus', or any other image manipulation utility that did not save the EXIF Marker as the first marker in the file.

10.18 Version 0.3

GENERAL

1. the exifdate utility has been added.

EXIFLIST

1. the option to output EXIF fields as an SQL INSERT statement
2. some command options have been changed to be more extensible, and be more consistent with UNIX conventions:
 - a. the '/l' option has been changed to '/o l'
 - b. the '/s' option has been changed to '/r'
 - c. the '/r' option has been changed to '/u'

11 Index

A

audio, extracting to .wav file, 46

C

character set
 default, 16
 definition, 16
character sets
 listing, 53
 setting, 16

D

date fields
 adding to, 29
 replacing, 29
Date Taken
 dd, 11
 hr, 11
 min, 11
 mm, 11
 mmm, 11
 sec, 11
 yy, 11
 yyyy, 11
dates field
 subtracting from, 29
Daylight Saving Time, 40

E

editable fields, definition, 32
environment variables
 used to set character sets, 18
 used to set EXIF comment field character set, 19
exifcopy, **24**
exifdate, **29**
exifedit, **32**
 limitations when no license key installed, 44
exiffile, **40**
exif-file, 21
exif-head, 21
exifkey, **44**
exiflist, **46**
exif-tail, 21

F

field
 adding, 32
 copying, 49
 listing valid values, 46
 nicknames, 11
 removing, 32
 selecting multiple fields, 12
 setting to match actual image values, 32
field list, **11**, 56
 default fields, 55
field value list, 36
file-name-template, 41

I

image files
 differences, 25, 38

L

last modified date, **40**
License
 feature limitations when no license installed, 44
License Agreement, 81
 Registered, 81
 Unregistered, 81
license key
 exifkey use, 44

M

Microsoft Excel, 58

N

nicknames, 11
 date-digi, 40
 date-mod, 40
 date-taken, 40
 exif-common, 12
 file-dir, 11
 file-name, 11
 file-name-audio, 11, 12
 file-name-backup, 12
 file-name-base, 11
 file-name-ext, 11
 file-name-full, 11
 file-name-thumb, 12

EXIFutils Command Reference

file-size, 11
iptc, 12

O

option string, 10

S

Software License Agreement, 81
Summer Time. *See* Daylight Saving Time

T

template, 40
definition, 20
file-name-template, 41

in field value list, 36
section markers, 21
sectioned, 21
thumbnail image
adding, 32, 38, 39
extracting to a file, 46
removing, 32, 38, 39

U

UNICODE
EXIF comment field, 19

W

wav files, extracting audio to, 46